Synthesis of surface snowfall rates and radar-observed storm structures in 10+ years of Northeast US winter storms

Laura M. Tomkins¹, Sandra E. Yuter^{1,2}, Matthew A. Miller², Mariko Oue³, and Charles N. Helms^{4,5}

¹Center for Geospatial Analytics, North Carolina State University, Raleigh, NC, 27695, USA

²Department of Marine, Earth, and Atmospheric Science, North Carolina State University, Raleigh, NC, 27695, USA ³School of Marine and Atmospheric Sciences, Stony Brook University, State University of New York, Stony Brook, NY, 11794, USA

⁴Earth System Science Interdisciplinary Center, University of Maryland, College Park, College Park, MD, 20740, USA ⁵NASA Goddard Space Flight Center, Greenbelt, MD, 20771, USA

Correspondence: Laura M. Tomkins (lauramtomkins@gmail.com)

Abstract.

Winter storms can cause disruptions in the densely-populated regions of the Northeast United States. Mesoscale snow bands embedded within winter storms are often the main focus of snowfall forecasts and analyses. While primary bands are associated with frontogenesis, multi-bands are found in environments with both frontogenesis and frontolysis. This study investigates the

- 5 relationship between observed surface snowfall rates and local enhancements in radar reflectivity (i.e., mesoscale snow bands) using data from 264 storm days over 11 winter seasons (2012-2023). We compare hourly surface snowfall rates obtained by ASOS weather stations with the area \times time fractions of locally-enhanced reflectivity features and of all echoes passing over the 25 km radius vicinity of the surface observation. Our analysis focuses on non-orographic snow storms with surface winds $< 5 \text{ m s}^{-1}$.
- Our findings show that most of the time snow rates are low (75% of hours had liquid equivalent snow rates less than 1 mm hr⁻¹). Heavy snow rates (> 2.5 mm hr⁻¹ liquid equivalent) are rare (< 4% of observations). When enhanced reflectivity features pass over a location, only 1 out of 4 hours have heavy surface snow rates. High spatial resolution vertical cross sections from airborne radar obtained during the NASA IMPACTS field campaign and rapid update RHIs from ground-based radar demonstrate that enhanced reflectivity features in snow aloft are tilted and smeared on their way to the surface as their constituent snow particles are dispersed laterally by the horizontal winds within the storm. The duration of all snow echo over a location is useful in determining where higher snowfall accumulations may occur.</p>

1 Introduction

The intersection of high population density and winter weather in the Northeast United States yields more frequent disruptive societal impacts as compared to winter weather in other US regions (Kocin and Uccellini, 2004; Novak et al., 2023; Guarino

20 and Firestine, 2010). This geographic region encompasses the states of Pennsylvania, New Jersey, New York, Connecticut, Rhode Island, Massachusetts, Vermont, New Hampshire, and Maine and includes the urban corridor spanning the cities of

Philadelphia, New York, and Boston. The geography includes portions of the Appalachian Highlands and Atlantic Coastal Plain (Fenneman, 1928). In general, storms in the region have negligible to weak orographic forcing, excepting a few areas with higher peaks.

- 25 US National Weather Service (NWS) forecasters use a variety of methods to predict snowfall accumulations. From numerical models, they use ice water context (IWC) as well as the presence of banded features in simulated reflectivity to estimate quantitative precipitation (Radford et al., 2023). For nowcasting, NWS forecasts use observed radar reflectivity to determine locations of heavy snow (David Novak, personal communication).
- Much previous work on diagnosing heavy snow rates in northeast US winter storms has focused on mesoscale *snow bands*, elongated features of enhanced radar reflectivity observed by operational scanning radars. Snow bands that are longer than 200 km are called primary bands and are associated with strong frontogenesis at low- and mid-levels in the storm (Novak et al., 2004, 2010; Ganetis et al., 2018; Kenyon et al., 2020; Baxter and Schumacher, 2017). Bands that are shorter than 200 km and typically occur in groups are known as multi-bands. Previous work related to winter storms in the northeast US has often focused on primary bands and understanding their associated physical mechanisms (e.g. Novak et al., 2004, 2008, 2009, 2010;
- 35 Novak and Colle, 2012; Kenyon et al., 2020; Stark et al., 2013). The relationship between multi-bands and frontogenesis is not clear as multi-bands are found in a wide range of frontogenesis environments including negative values (frontolysis) (Ganetis et al., 2018; Nicosia and Grumm, 1999; Connelly and Colle, 2019). Han et al. (2007) examined the precipitation structure of 2 winter storms and found that couplets of frontogenesis and frontolysis were present in the vicinity of both the occluded front and the warm front. The physical mechanisms and relative importance of different types of instabilities (potential, conditional,
- 40 shear, conditional symmetric) to multi-band production is a topic of active research (e.g. Shields et al., 1991; Ganetis et al., 2018; Leonardo and Colle, 2024; Varcie et al., 2022; Zaremba et al., 2024).

Case studies of northeast winter storms have usually focused on extreme events with high snowfall accumulations and strong frontogenesis (e.g. Picca et al., 2014; Varcie et al., 2022; Ganetis and Colle, 2015; Novak et al., 2008; Han et al., 2007; Colle et al., 2014; Clark et al., 2002; Lackmann and Thompson, 2019). But the relative prominence of different physical processes

- 45 in an extreme event may not be analogous to that for a more typical, weaker winter storm. The practice of generalizing that extreme events are representative of typical events implies that extreme events are a clearer, more "pure" representation of the key physical processes rather than a low probability juxtaposition of circumstances that amplify snowfall. The assumption of representativeness of extreme events for more typical winter storms needs to be evaluated with evidence from a large sample size.
- 50 While most of the snow band literature has focused on the northeast US, non-orographic snow bands have been documented in winter storms across the world. Lake/sea-effect snow banding has been investigated in Europe and Japan (Mazon et al., 2015; Norris et al., 2013; Fujiyoshi et al., 1998; Murakami, 2019; Sato et al., 2022). Winter storms in eastern Asia (China, Russia, Korea) also exhibit banded features (Zhao et al., 2020).

We use NWS Next-Generation Radar (NEXRAD) radar and ASOS data from 264 snow storm days in the northeast US to determine if the relationships illustrated in outlier case studies between radar observed snow bands and heavy surface snowfall withstand scrutiny with a large data set. We also examine recent field campaign observations of the detailed vertical structures

within winter storms from airborne radars deployed during the recent NASA Investigation of Microphysics and Precipitation for Atlantic Coast-Threatening Snowstorms (IMPACTS) field campaign (McMurdie et al., 2022) and from ground-based radars at Stony Brook University (KASPR; Oue et al., 2017).

- 60 There are several complicating factors in the analysis of winter storms using weather radar observations. Increases in radar reflectivity in snow do not necessarily equate to increases in mass per unit volume (Table 1). Aggregation and partial melting increase the radar reflectivity but do not change the mass per unit volume. Additionally, there are important differences between the 3D structures of enhanced reflectivities in rain versus snow. In warm-season precipitation systems the 0°C level is 3 km altitude or more above the surface and it is reasonable to deduce that stronger locally-enhanced radar reflectivity features a
- 65 few kilometers above the surface are associated with higher rain rates at the surface. The typical fall speeds of raindrops (\sim 2- 8 m s^{-1} . depending on raindrop size) often yield nearly vertical columns of enhanced reflectivity features in rain layers. In contrast, the slower fall speed of snow, ($\sim 1 \text{ m s}^{-1}$, equivalent to 33 minutes to fall 2 km) yields sufficient time for the the advection of the snow by horizontal winds, which are typically $>10 \text{ m s}^{-1}$, to form curved ice streamers (Wexler, 1955; Wexler and Atlas, 1959). Falling snow particles can be blown sideways more than 50 km horizontally from the locations where they 70 first achieve precipitation size near the top of the storm.

Further, there is a large variation between observed ice water content (IWC) and reflectivity in ice clouds and light snow (Zaremba et al., 2023). Coincident observations of IWC and radar reflectivity collected during research aircraft flights as part of the Seeded and Natural Orographic Wintertime Clouds: the Idaho Experiment (SNOWIE) field campaign in the mountains of Idaho (Tessendorf et al., 2019) illustrate the joint frequency distribution of this relationship (Fig. 1). These IWC and Z data

75 for surface-snow-producing clouds over the mountains of Idaho do not include any partially melted particles but may include aggregates. For reflectivities > 0 dBZ, which usually contain some precipitation-size falling ice particles, IWC generally increases as Z increases. But given the spread of the observed values, there is at least a factor of two uncertainty in the volumetric ice mass as a function of radar reflectivity (Fig. 1; Zaremba et al., 2023).

The overarching goal of this study is to explore and understand the relationships between surface snow rates and locallyenhanced reflectivity features (i.e. snow bands) in winter storms. The key finding is that locally enhanced linear features (i.e. 80 mesoscale snow bands) in operational scanning radar reflectivity within northeast US snow storms (which exclude orographic and lake effect snow storms) are usually not associated with heavy surface snow rates.

2 **Data and Methods**

2.1 10+ year Winter Storm Dataset

We use observations from 264 storm days in the northeast US from over 10 years (2012-2023) to ensure we are studying the 85 relationships over a large representative sample. Following the methodologies of Hoban (2016) and Ganetis et al. (2018), we define a winter storm as any date within the months of October to March for the years 2012-2023 where at least 25.4 mm (1 inch) of snow depth was reported over a 24-hour period at at least two out of 14 stations shown in Fig. 2b. We used a threshold of 25.4 mm to include a wide range of storms in our analysis and not only those that produce a large snow accumulation. The

- 90 daily snow depth data at each station was gathered from the Global Historical Climatology Network daily (GHCNd) database (Menne et al., 2012). We selected the subset of 14 stations to focus on storms that impacted the more densely-populated regions of the northeast US and to minimize the inclusion of storms that were predominantly lake-effect snow events. While the majority of the stations we use to define winter storm events are close to the coast, it is possible that by using the Albany, NY and Binghamton, NY stations that some lake-effect events are included in our dataset. Lake-effect snow bands passing overhead
- 95 have a documented relationship to heavier snow rates (Kristovich et al., 2017; Kosiba et al., 2019; Mulholland et al., 2017) so their inclusion in the data set could slightly bias the results toward a stronger relationship between snowbands and heavier surface snow than is true for stations further from the Great Lake shores.

The years 2012-2023 were chosen since 2012 is the start of the period when dual-polarization radar data are available from US NWS radars. Use of dual-polarization products allows us to remove melting and mixed precipitation observations, often confused for heavy snow, from our analysis (discussed in Sec. 2.1.3). The full list of storms are tabulated in Table S1 in the Supplementary Material.

2.1.1 Hourly surface station observations

Hourly observations from 29 ASOS stations in the northeast US are used to quantify the liquid equivalent snowfall rates during each winter storm day (Fig. 2). The hourly snowfall rates represent hourly liquid equivalent *accumulation* and are not instantaneous snow rates. ASOS data are obtained from the online MADIS database (https://madis-data.ncep.noaa.gov/index.shtml). Measuring snow with precipitation gauges can be challenging as snow is easily blown sideways by the wind

- and doesn't always make it into the gauge (Bruce and Clark, 1966; Groisman and Legates, 1994; Rasmussen et al., 2012; Kochendorfer et al., 2022). To ensure we are getting the best measurements, we are only using ASOS stations equipped with all-weather precipitation accumulation gauges (AWPAG) as these gauges are more skilled at measuring liquid equivalent snow
- 110 accumulation than other types of gauges (Martinaitis et al., 2015). The AWPAG sensors are equipped with Tretyakov or double Alter style shields, which are more accurate at measuring frozen precipitation than gauges with no shields (Rasmussen et al., 2012). AWPAG sensors do not have a heated rim and thus are subject to capping, although it is difficult to estimate how often this occurs in our dataset (Martinaitis et al., 2015). If capping does occur, no snow would be reported for an hour, resulting in an underestimation of the snow accumulation for that hour. Partial capping can also occur and would result in an underestimation
- 115 of snow for a period of time followed by an overestimate once the cap releases (Baker Perry, personal communication). To further ensure that we are using reliable observations, only quality-controlled observations when the wind speed is $< 5 \text{ m s}^{-1}$ are used in our analysis (Rasmussen et al., 2012). The collection efficiency of frozen precipitation is 1.0 at a wind speed of 0 m s⁻¹ and drops to 0.25 at a wind speed of 6 m s⁻¹ for double Alter-shielded gauges which is why we chose a threshold of 5 m s⁻¹ (Rasmussen et al., 2012). The wind speed threshold removes ~45% of hourly snow observations. The distribution of
- 120 removed measurements is relatively uniform over the entire range of precipitation rate observations (see Fig. 2.6 in Tomkins (2024)). Observations are only used in the analysis if the station has reported snow for at least 4 hours to ensure we are using observations from consistent snow observations, and not any short-lived, low-impact events.

Following the guidelines of the Society of Automotive Engineers International Ground Deicing Committee and NCAR, we use a liquid equivalent precipitation rate threshold of 2.5 mm hr^{-1} to distinguish heavy snow from light (<1 mm hr^{-1}) and

125

moderate (1-2.5 mm hr⁻¹) snow (Rasmussen et al., 2001). We will use the term *heavy* to describe the snow rates >2.5 mm hr⁻¹ liquid equivalent.

An example time series of liquid equivalent precipitation rates from Boston, MA on 7 February 2021 is shown in Fig. 3. Hourly observations that are used in the analysis are represented by a blue bar spanning the hour that the precipitation accumulates. Trace values (0 mm hr^{-1}) are considered in the analysis (17 UTC), while observations when no precipitation fell are not (06-16 UTC). The example also shows observations not used in the analysis where the wind speed threshold is

130 fell a

exceeded (22 UTC - 0 UTC) (plus sign in Fig. 3).

2.1.2 Regional radar mosaics

We use radar observations from the NWS NEXRAD network in the northeast US to analyze features of the radar reflectivity field in winter storms. All NEXRAD data were obtained from the NOAA archive on Amazon Web Services (Ansari et al., 2018). The NEXRAD radars scan 360° in azimuth over sets of elevation angles that vary with the selected volume coverage pattern. In this analysis we use the elevation angle at 0.5° above the horizon as 0.5° is the lowest angle common to the different volume coverage patterns. We interpolate the single elevation to yield a 2D grid using Cressman weighting (Cressman, 1959, for full details see Tomkins et al. (2022)). We found that interpolation among elevation angles, as is done in the NWS 3D interpolated radar reflectivity product (Smith et al., 2016), often smoothed out gradients bounding locally enhanced reflectivity

140 features of interest.

Our radar data processing utilizes the open-source Python Atmospheric Radiation Measurement (ARM) Radar Toolkit (Py-ART) developed by the Department of Energy ARM Climate Research Facility (Helmus and Collis, 2016). We combine data from multiple radars in the northeast US into a mosaic on a Cartesian grid over an area of 1202 km x 1202 km with 2 km horizontal grid spacing. The radars used to create the mosaics and an example mosaic are shown in Fig. 2. Regional mosaics

145 are generated for 5-10 min time steps during each storm. Tomkins et al. (2022) details the quality control, interpolation, and other data processing steps to produce the mosaics.

2.1.3 Objective detection of snow bands

Identifying and locating regions of locally-enhanced reflectivity can often be subjective and inconsistent from observer to observer. To mitigate this, we developed a technique that objectively identifies local enhancements in radar observations (Tomkins

- 150 et al., 2024). Previous methods to detect enhancements in enhanced reflectivity features in the rain layers of storms, such as convective precipitation cells, did not work well for detecting snow bands. Locally-enhanced reflectivity features in snow have more diffuse edges and smaller relative differences compared to the background values than convective cells in rain layers. The technique we employ uses two adaptive thresholds to identify objects based on their distinctness (faint or strong) from the background average. We identify objects in a snow rate field that has been rescaled from reflectivity in order to define local en-
- 155 hancements based on spatial gradients that are roughly linear in snow rate. To rescale the reflectivity, we use the wet snow Z-S

relationship from Rasmussen et al. (2003); $Z_e = 57.3S^{1.67}$ where Z_e is equivalent radar reflectivity with units of mm⁶ m⁻³ and S is snow rate with units of mm hr⁻¹. Note that the snow rate obtained from this relationship represents an instantaneous rate and is not liquid-equivalent unlike the data reported from the ASOS stations. The algorithm outputs a feature detection field which classifies each grid point with radar echo as either part of a "faint feature", a "strong feature", or "background".

160 Details on the feature detection algorithm including multiple examples of reflectivity fields, snow rate fields, and the identified features are provided in Tomkins et al. (2024). Example reflectivity, snow rate and feature classification fields are shown in Fig. 4.

The relationship between reflectivity and liquid equivalent snow rate has large uncertainty as it depends on the ice particle shape, density, degree of riming, aggregation, and terminal velocities of the snow particles present. It would not be suitable to

- 165 use the quantitative values from a single Z-S relationship (e.g. Fujiyoshi et al., 1990; Mitchell et al., 1990; Rasmussen et al., 2003; Matrosov et al., 2008; von Lerber et al., 2017; Wen et al., 2017). We developed our technique based on the method of Krajewski et al. (1992) who used an area-threshold method to estimate mean areal rainfall using radar reflectivity observations. Krajewski et al. found that when there is high uncertainty in the Z-R relationship, the rainfall estimates from the area-threshold method perform significantly better than the estimates from the Z-R relationship. Our area × time fraction method estimates
- 170 space-time integrals from quantities derived from radar reflectivity spatial patterns thereby avoiding issues that would result from using a highly uncertain transformation from reflectivity to snow rate. Yeh and Colle (2025) compared several different identification methods for identifying snow bands in winter storms and found that object-based methods performed better than methods using an absolute or variable reflectivity thresholds.
- Transitions between snow, rain, and partially-melted snow are common in northeast US winter storms which complicates
 the interpretation of reflectivity since melting and mixed precipitation have higher reflectivities than volumes of only ice or only liquid particles of the same mass. We identify regions of mixed or melting precipitation by combining information from the radar reflectivity and correlation coefficient dual polarization fields (Tomkins et al., 2022). We remove regions identified as mixed and melting precipitation from our analysis and reduce the visual prominence of these regions in our visualizations using "image muting" (Tomkins et al., 2022). The image muted regions are depicted in gray scale in regional maps shown as
 part of subsequent figures.

2.2 Area \times Time fraction

185

A main goal of this project is to understand the impact of locally-enhanced reflectivity features on the hourly surface snow rates. To accomplish this, we focus on the echo classified as features (from the methods discussed in Sec. 2.1.3) within 25 km of the ASOS station. The regional radar mosaics occur every 5-10 minutes, so in order to distill the echo area over the hour, we computed an integrated metric called the area \times time fraction. Figure 5 illustrates the echo area data that goes into calculating the area \times time fraction. We examine separately the *feature area* \times *time fraction* calculated for the echo classified as features (both strong and faint) and the *all echo area* \times *time fraction* (strong and faint features plus background echo).

To calculate the area \times time fraction we sum the area surrounding the station within 25 km radius for that hour and then we divide by the total seconds in an hour and the total area surrounding the station within 25 km which yields a unitless fraction.

Fig. 5d demonstrates 3 scenarios (of many) that would yield an area \times time fraction of 0.5. A feature area \times time fraction of 1 would indicate the entire surrounding region is filled with feature echo for the entire hour and a fraction of 0 would indicate no feature echo in the surrounding region for the entire hour.

2.3 Low pressure center tracks

- For each winter storm, we computed the low-pressure center storm track from the ERA5 hourly reanalysis mean sea level
 pressure (Hersbach et al., 2020) using the methods of Crawford et al. (2021). We subset the global 0.25° resolution ERA5 mean sea level pressure (MSLP) field to the region of Eastern North America (-90 to -60°E, 25 to 55°N). For a given winter storm day, we track over ± 1 day to capture the full evolution of a given low pressure system. To find a single minimum for a given time, we first find all the local minima in the MSLP field using a 200 km search radius. Unlike Crawford et al. (2021), we are using the ERA5 data in native coordinates, so the grid size in km varies slightly between grid boxes. To avoid finding pressure minima that skip along edges of our our defined Eastern North America region, we only consider minima
- where at least 75% the 200 km search radius is within the region. Following Crawford et al. (2021), minima found from the MSLP field are only considered if they have a pressure gradient of at least 7.5 hPa/1000 km. We compared the low pressure center minimum to the set of pressures at 200 km range from the low pressure center. To meet the threshold criteria, the mean difference between minimum pressure and the set of pressures at 200 km range must be at least 1.5 hPa. Once all the local
- 205 minima have been found for the entire period, we then loop through the period again to select a single minimum for each time since there may be no minimum, one minimum, or multiple minima for each time. In the case of multiple minima we choose the minimum that meets most of the following: minimum which is closest geographically to the previous minimum, minimum with the strongest pressure gradient, and the minimum with the lowest MSLP value. If the closest, strongest, and deepest minima are all different points, we choose the closest minima. If the next point is more than 200 km away from the
- 210 previous point, we consider this a new system and new track. We filter the tracks to remove tracks that travel less than 250 km or exist for less than 6 hours. Finally, we remove any points on the tracks where the MSLP is greater than 1010 hPa.

All tracks between 2012 and 2023 that meet our winter storm criteria defined in Section 2.1 are shown in Fig. 6. The density of tracks shows a clear tendency for low pressure centers to be near the coastline or over the ocean and to move southwest to northeast roughly parallel to the coast (Fig. 6). This pattern is consistent with climatological studies of cyclone tracks (e.g.,

215 Bentley et al., 2019). There is a lack of low pressure locations along/to the east of the Appalachian mountains which we suspect is due to our criteria for defining a snow storm for this study (Sec. 2.1). Since we are only looking at events where stations along the coast and slightly inland in the northeast US produce snow, tracks along the Appalachian corridor may not produce enough snow within our region of interest to be considered in our dataset.

Hourly liquid-equivalent snow rates from ASOS stations are plotted relative to the low pressure centers in Fig. 7. Most of the winter season storms with appreciable snow had low center tracks offshore of the northeast US (Fig. 6). This tendency for the low tracks to be offshore and the shape of the coastline yields a geographic bias of the sample to favor observations in the northwest quadrant relative to the low pressure center (Fig. 7). There is sufficient density of observations in the northwest quadrant to suggest a gradient in snow rates with higher values more common closer to the low pressure center. The northwest quadrant typically contains the occluded front and northeast quadrant typically contains the upward sloping frontal boundary ahead of the warm front. Frontogenesis is typically present in both the NE and NW quadrants (Novak et al., 2004). Additionally, for northeast US winter storms the near surface air in these quadrants is more often cold enough to support snow as compared to the southwest quadrant cold frontal region that drapes further south and often yields rain.

The northeast quadrant, where frontogenesis typically occurs associated with the warm front, had the highest median and mean hourly snow rates among the four quadrants (see Table 6.1 in Tomkins (2024)). The low-centric spatial distributions of liquid equivalent snow rate align with our expectations given typical spatial patterns of large-scale lifting associated with different storm stages (Fig. 7). More active riming closer to the low, as found in Colle et al. (2014), would be consistent with heavier liquid water equivalents all other factors being equal but ASOS data does not let us assess this hypothesis.

2.4 NASA IMPACTS Airborne Radar Data

255

Vertical cross sections collected from radars aboard the NASA ER-2 aircraft deployed during the NASA IMPACTS field campaign (McMurdie et al., 2022) illustrate typical vertical structures and horizontal wind profiles observed in winter storms. There were 3 radars (4 frequencies total) that sampled storms during the campaign; EXRAD, HIWRAP (2 wavelengths), and CRS. EXRAD and HIWRAP are precipitation radars while the CRS is a cloud radar. The cloud radar is more sensitive to smaller ice particles than the precipitation radars and has a smaller radar resolution volume size which is capable of observing finer-scale features (see Table 2 for details including the resolution of each radar at 10 km distance). The examples we present

- 240 here have a reflectivity panel from the radar with the longest wavelength that was available (usually EXRAD, and HIWRAP Ku-band if EXRAD was not available) as well as velocity and spectrum width from the shortest wavelength that was available (usually CRS, and HIWRAP Ka-band if CRS was not available). Because the sensitivity is different for each radar (see Table 2) there is echo that is present in the velocity and spectrum width field that isn't present in the reflectivity field. When available, Velocity Azimuth Display (VAD) horizontal winds derived from the EXRAD scanning beam (Helms et al., 2020) are shown
- on the reflectivity cross sections and summarized with Contoured Frequency by Altitude Diagrams (CFADs; Yuter and Houze, 1995) in terms of joint distributions of wind speed and height and wind direction and height. The latter are shown in polar coordinates.

The ER-2 ground speed varies depending on wind speed and direction at flight level (i.e. slower in head winds and faster in tail winds). On average this value is ~200 m s⁻¹. Actual ground speed values along each flight leg are converted to distance for plotting purposes. Section 3.2.2 shows 5 example transects during the NASA IMPACTS project. An additional 57 ER-2 transects with snow at the surface can be found in the supplement.

The velocity and spectrum width fields are shown to provide additional context for the examples. The velocity field can be used to infer regions of rain versus snow and Doppler spectrum width is a proxy for turbulence (Rauber and Nesbitt, 2018). To correct the spectrum width field to yield high quality data, we use equation 7 in Heymsfield et al. (1996) to isolate the spectrum width of the hydrometeors and remove the spectrum width broadening caused by the aircraft speed. In some cases, this correction causes the spectrum width numeric value to become $\leq 0 \text{ m s}^{-1}$ (i.e. a nonphysical value; see blank echo in Fig.

15c) which is ignored in the plotting as it represents signal below the noise floor.

2.5 Stony Brook University Ka-band radar

Rapid update range-height indicator (RHI) scans from the Ka-band (35 GHz) scanning fully polarimetric radar (KASPR)

260 located at Stony Brook University further illustrate the evolution of enhanced features in a winter storm (Figs. 18 and 19). The data from the ground-based KASPR radar has finer vertical and horizontal spatial resolution than the ER-2 airborne radar data (Table 2).

The KASPR RHIs scan up and over the radar such that the azimuth angle of the radar beams within the RHI varies from $\sim 0.5^{\circ}$ elevation angle in the southern part of the domain up to vertically-pointing right over the radar and then back down to $\sim 5-10^{\circ}$ elevation angle at the northern horizon in about 30 seconds.

When the radar beam is vertical or nearly vertical, the measured values of Doppler velocity and spectral width combine vertical air motions with precipitation particle fall speeds. When the radar beam is closer to horizontal, the measured motions are more indicative of the horizontal wind.

The effect of the changing component of the wind that is sampled as the radar beam elevation angle changes is particularly noticeable in the RHIs of Doppler velocity data (Fig. 18b and 19b). Plotted velocity values in a given layer tend to be strongest at the left and right edges of the RHI where the beam is more horizontal and peter out as the beam becomes more vertical near the center of the RHI plot. Whereas in the ER-2 radar vertically-pointing data the Doppler velocity values were plotted with a range from -5 to 5 m s⁻¹, in these RHI plots, which are dominated by strong horizontal winds, the range plotted is -45 to 45 m s⁻¹. In the RHI plots, layers with low values of Doppler velocity indicate that the horizontal wind direction is close to perpendicular to the beam (i.e. in or out of the plane of the cross-section). A similar but less dramatic impact of beam angle on the measurements is apparent in the RHI spectral width plots. Although turbulence is usually close to isotropic, the combination of the air motion velocity spread with the strong signal from the often narrower precipitation fall speed spread tends to reduce the net spectral width magnitudes when the beam is pointed nearly vertical.

3 Results

280 The following results show that locally-enhanced reflectivity features are not consistently related to heavy surface precipitation rates. Most of the time, precipitation rates are low, even when locally-enhanced reflectivity features are present. Vertical cross sections from airborne and ground-based radars illustrate that the local enhancements in reflectivity within snow are tilted and smeared on the way to the surface. The lack of vertical continuity of reflectivity enhancements in snow helps to explain the lack of relationship between local enhancements observed by operational scanning radars and heavier surface snow rates.

285 3.1 Enhanced reflectivity features in horizontal maps and their relation to surface snowfall rates

Figure 8a shows the 2D distribution of all features (faint + strong) area \times time fraction versus liquid equivalent precipitation rate. The quadrants in Fig. 8a are summarized in a bar chart in Fig. 8c. Considering the previous literature focused on snow banding in winter storms, we were expecting to see a trend in the joint distribution indicating a relationship between increasing

feature area \times time fraction and increasing precipitation rate, however this is not the case for the large sample size examined

in this study. Most points (89.1%) are clustered in the lower left box where both area \times time fraction and precipitation rate are 290 low. There are some observations where the area \times time fraction and precipitation rate are high, however they only account for $\sim 1.5\%$ of the observations when the feature area \times time fraction is > 0.

Heavy hourly snow rates in northeast US winter storms are rare. Over all the hourly observations presented here, heavy snow rates (> 2.5 mm hr⁻¹) occurred < 4% of the time. This analysis indicates that anecdotal evidence from case studies

in the literature showing a strong relation between heavier snow at the surface and enhanced reflectivity features aloft is not 295 representative for a large sample size of 7606 hours, 264 storms, obtained over 11 years. Figure 8a.c indicates that *equating* snow bands with heavy snow will usually lead to over prediction of hourly snowfall rates. Our large sample size shows that 3 out of 4 times situations with feature area \times time fractions > 0.5 have liquid equivalent snow rates < 2.5 mm hr⁻¹. More hours with heavy snow at the surface occurred associated with smaller feature areas (364 hours) as compared to larger feature areas 300 (113 hours).

Since locally-enhanced reflectivity features are not particularly helpful at identifying regions of heavy snow rates, we calculate the area \times time fraction for *all echo areas* to see if there are patterns present (Fig. 8b,d). The patterns in this 2D distribution indicate that heavy snow rates (> 2.5 mm hr⁻¹) are more common when there is a large echo area \times time fraction (i.e. there is a lot of echo surrounding the station for a longer duration). This suggests that it is more useful to focus on the duration of all echo over a location rather than the size, duration, and location of just the locally-enhanced reflectivity features (i.e. snow

- bands) for deducing where higher snowfall accumulations may occur. The distribution of snowfall rates has a strong skewness to low values, 75% of the time it is snowing at a rate no more than 1 mm hr^{-1} . So even if there is enhanced reflectivity feature area it is more likely associated with a low snow rate than a heavy snow rate.
- To provide context for the joint frequency distribution, we present representative examples of each quadrant in Fig. 8a. The 310 first is an example when high feature area \times time fraction and heavy snowfall are observed over an hour (Fig. 9). Panel a in Fig. 9 illustrates a large, strong feature over the Albany, NY ASOS station which contributes to a feature area \times time fraction of 0.62 over the hour and coincides with an hourly liquid equivalent snowfall rate of 3.6 mm hr^{-1} . Later in this event, there are several hours at this station that were not included in our analysis because the wind speed was too high (blue plus signs in Fig. 9c). The scenario of high feature area, heavy snowfall occurs in only 1.5% of hours in our dataset. In this specific example, the feature resembles a primary band and is likely forced by frontogenesis. 315

The second example is from an event on 26 January 2021 where several strong and faint features are moving through the region (Fig. 10a). In the snapshot in Fig. 10a, there is a strong feature over the Providence, RI ASOS station which contributes to a feature area \times time of 0.58 over the hour (Fig. 10). While the feature area \times time fraction is high (> 0.5) in this example, the snow rate is 2 mm hr^{-1} (Fig. 10c). Scenarios with high feature area \times time fraction and a low/moderate snow rate represent 4.6% of hours in our dataset.

320

305

The next example from 2 February 2021 represents the most common occurrence in our dataset where a low feature area \times time fraction and a low/moderate snow rate is observed over the hour. This example from Lebanon, NH shows only a small faint object in the vicinity of the ASOS station and has a feature area \times time fraction of 0.2 over the hour and a snow rate of 1.3 mm hr⁻¹ (Fig. 11). For the remainder of the event there are no features in the vicinity of the ASOS station and the snow rate remains low/moderate (Fig. 11c). Scenarios when the feature area \times time fraction is low and the snow rate is low account for 89% of observations.

Lastly, we have an example when the feature area \times time fraction is low but the snow rate is heavy which occurs in 4.8% of our observations. This example from Worcester, MA shows an hour where the liquid equivalent precipitation rate was 9.7 mm hr⁻¹ but the feature area \times time fraction was only 0.12 (Fig. 12). There are a few faint features in the area, but overall the echo is patchy. The all echo area \times time fraction was 0.9. The time series shows that there are several times in this event where the snow rate was heavy but there were little or no features present over the station. Scenarios with small feature area \times time fraction of background echo rather than mostly locally-enhanced reflectivity features. It is also possible that in this case that the snow storm is shallow and the radar beam height is above any locally-enhanced features.

335 3.1.1 Sensitivity Tests

We tested the sensitivity of the results in Fig. 8 by varying various thresholds used in the calculations and these adjustments did not appreciably change our results (Figs. 5.10-5.14 in Tomkins, 2024). We varied the radius around the ASOS station to 12.5, 25, and 50 km to account for the horizontal advection of snow, the time lag between the radar and ASOS observations (0-, 1-, and 2-hour), and the number of hours of precipitation accumulation (1-, 2- and 3- hours). We also subset by radar beam altitude

above the ASOS station, and percent of mixed precipitation echo removed over the hour. For example, applying thresholds based on the average beam height of the radar echo changed the fraction of hours in the high area \times time fraction-heavy snow rate category to 1.8% for \le 1000 m, 1.7% for \le 2000 m, and 1.5% for \le 3000 m. While these sensitivity tests yielded slightly different numbers for each quadrant in the joint distributions of feature area \times time fraction versus liquid water equivalent precipitation rate, the key findings from Fig. 8 are robust relative to the tested variations.

345 3.2 Vertical structures in reflectivity are tilted and smeared

The lack of relationship between ground-based-scanning-radar-observed locally-enhanced reflectivity features and snow rates indicates that the radar observations above the surface are not necessarily consistent with snow rates observed directly below at the surface. As discussed in Sec. 1, there are several factors that complicate the relationship between reflectivity and snowfall rate as compared to reflectivity and rain rate: changes in radar reflectivity in snow (especially aggregation and partial melting) do not necessarily equate to changes in ice mass (Table 1), slow fall speeds of snow yield time for advection of snow over 10s of kilometers by horizontal winds as it falls to the surface, and there is a large spread in observed values for a given IWC and its associated radar reflectivity.

High spatial resolution vertical cross-sections of radar data from winter storms indicate that snow rarely falls straight down to the surface. Locally enhanced reflectivity features in snow tend to be tilted and smeared by the wind shear (changes in the wind speed and direction with height) between echo top and the surface. In the following two sections, we feature examples of high

355

vertical resolution cross-sections within snow storms that illustrate the lack of vertical column continuity in locally-enhanced reflectivity.

3.2.1 Vertical structures observed by airborne radar data

360

As aircraft equipped with vertical-pointing radar fly along, they obtain a slice through the atmosphere. For the NASA ER-2 which has an ground speed of $\sim 200 \text{ m s}^{-1}$, each 50 km in distance along the leg represents 5.6 minutes of flight time. Adjacent portions along the track can be considered to be within a few minutes coincident in time.

The first example from 5 February 2020 in the Midwest illustrates several types of variations in the structures in reflectivity field (Fig. 13). At the beginning of the transect, when the aircraft is traveling from the edge of the echo in the regional map (Northern Illinois; Fig. 13d) the vertical cross sections indicate that the echo aloft is not reaching the surface (0-40 km, 0-1 km

- 365 altitude in Fig. 13a). At ~90 km along flight track, there are regions where there is echo reaching the surface but "holes" in the echo aloft. Other regions along the cross section show consistent echo through the vertical column and indicate lots of wind shear illustrated by the wind barbs and bends in the local variations of the reflectivity field itself (i.e. 125-175 km in Fig. 13a). The wind barbs in the VAD profiles indicate the direction and speed that the wind is coming from and correspond well to the patterns in the reflectivity field. The CFADs summarize the distributions with height of direction and speed of the winds in
- 370 the VAD profiles along the flight leg. It is important to note that the cross sections are plotted in a 3:1 aspect ratio (3 units in vertical to 1 unit in horizontal distance) so features that are tilted appear to be more vertical in the plots (see triangle icons next to Fig. 13c for visualization). An example transect showing a comparison between a 1:1 aspect ratio and a 3:1 aspect ratio is available in the Supplementary Material. CFADs of the wind speed (Fig. 13e) and wind direction (Fig. 13f) along the track indicate considerable vertical wind shear. Horizontal wind speeds reach around 30 m s⁻¹ at 5 km altitude near the top
- of the echo. The wind direction at 5 km altitude is roughly perpendicular to the direction the aircraft is traveling indicating that snow particles forming aloft will be transported out of the cross-section as they descend to the surface (Fig. 13b, c). While the human eye would like to connect structures through the entire depth of the echo, this is deceptive as spatial patterns in the lower portion of echo are the result of features at higher altitudes that are unseen (upwind and perpendicular) in the depicted cross-section.

The next example from 7 February 2020 shows a transect over New York (Fig. 14). In this example, the reflectivity is more uniform compared to the previous example (Fig. 14a). The aircraft is traveling westward from a region of higher reflectivity in central New York to a region of weaker reflectivity in western New York (Fig. 14a, d). This case was examined in Colle et al. (2023) for the lack of snow banding despite considerable frontogenesis present (values > 10 K (100 km)⁻¹ (3 hr)⁻¹). The CFADs of the wind speed and direction from the transect indicate speed shear and some directional shear (Fig. 14e,f). Similar

385

to Fig. 13, the wind direction is roughly perpendicular to the direction the aircraft is flying, indicating that the particles forming aloft are advected away from the flight path – and hence the vertical plane of the cross-section – as they fall (Fig. 14).

An example from 23 January 2023 shows a case where the aircraft flew parallel to strong, banded features in Maine and New Hampshire (Fig. 15). The reflectivity cross section shows ice streamers that are tilted as they approach the surface. The top of the ice streamers are likely generating cells associated with overturning circulations near cloud top (Fig. 15a). The velocity and

- 390 spectrum width cross sections indicate some overturning circulations near echo top between 150-200 km along the flight track (Fig. 15b,c). A non-uniform beam filling (NUBF) correction was applied to the velocity data and the circulation features show up in all wavelengths indicating that these velocity features are not NUBF (G. Heymsfield and M. Walker McLinden, personal communication, July 2023). As particles originating in the generating cells descend to the surface in ice streamers there are corresponding downward local enhancements in velocity (Fig. 15b), and locally higher spectral width values (Fig. 15c). The
- 395 aircraft is flying from NE to SW (Fig. 15d) and the horizontal winds in the layer between 5 km to 3 km altitude are from the SSW (Fig. 15a). Below 3 km altitude, winds turn to be from the N to ENE. The ice streamer advection in the 5 km to 3 km layer is close to being aligned with the flight path. This yields an aircraft radar cross-section that is more representative of the ice streamer's shape (Fig. 15a) than the previous examples where the ice streamer advection was more perpendicular to the flight path (Figs. 13a and 14a).
- 400 The remaining examples do not have VAD horizontal wind data available. We include a panel of the feature detection field instead for context. Figure 16 shows an example from a 300 km long flight track that flew over some faint enhanced reflectivity features in the Gulf of Maine. The regional radar reflectivity indicates that this storm had weaker and more patchy echo compared to the previous examples (Fig. 16d). The radar cross sections show shallower echo tops (~5 km altitude) compared to the previous examples. Between 125 km and 175 km along flight track, enhanced reflectivity features tilt to the right and 405 then to the left. There are weak echo holes throughout the cross-section.

Figure 17 shows an example from 17 February 2022 when the aircraft sampled a faint, banded feature over Lake Michigan (200-215 km along flight track). The flight track began over central Indiana (southeast) over surface rainfall which transitioned to surface snow at \sim 48 km along the flight track. This surface rain portion of the flight track is depicted as an image muted area in gray in Fig. 17d and has a radar bright band, and high Doppler velocities and spectral width in the rain layer between 0-48 km

- 410 (Fig. 17abc). Along the flight track within the snow layer between 6 and 2.5 km altitude, locally enhanced reflectivity features in snow tend to tilt to the right (towards northwest). At the northwest end of the flight track when the aircraft approaches the faint enhanced feature in the map (Fig. 17e), there is a layer of locally-enhanced reflectivity at ~2.5 km altitude between 150-250 km (Fig. 17a) with weaker to no echo below it. It is possible that the faint feature in the map manifests as the scanning radar intersects part of this elevated region of enhanced reflectivity.
- As part of this study, we examined all transects from the NASA IMPACTS campaign which included snow reaching the surface. In addition to Figs. 13-17 there are 53 additional transects which are shown in the Supplementary Material. IMPACTS flight legs that pass over regions with just rain at the surface are not included. For each transect in the supplement, we present the reflectivity, velocity, spectrum width, and LDR fields from the instrument with the shortest wavelength available (usually CRS, but occasionally HIWRAP Ku-band) and the reflectivity field from the instrument with the longest wavelength available
- 420 (usually EXRAD, but occasionally HIWRAP Ka-band). We include snapshots of the NEXRAD regional maps to provide context for the transects. If available, we include the VAD winds on the EXRAD reflectivity transects and CFADs of wind speed and direction to summarize. Each transect in the supplement is annotated with a vertical, dashed, black line which annotates where the enhanced reflectivity features are in the regional maps. Full details are available in the supplementary material. The additional examples shown in the Supplement are consistent with the findings illustrated in Figs. 13-17.

425 3.2.2 Sequences of vertical structures observed from ground-based radar data

Fast update RHIs from ground-based radar can obtain individual vertical cross-sections that complete in 10s of seconds and yield sequences of RHIs that can address storm evolution along the vertical plane at time scales < 1 minute. Within snow storms noticeable structural changes along a given vertical cross-section from a combination of storm advection and evolution usually have time scales of several minutes or more.

- 430 We show examples of fast update RHIs from the Stony Brook University KASPR from a storm that spanned 40 hours on 31 January to 2 February 2021. An animation of the sequence of RHIs for the full storm period, as well as two 2-hour periods corresponding to Figs. 18 and 19 are included in the Video Supplement. While RHIs have often been obtained by research radars in winter storms, this is one of the few examples with a fast enough update to discern how a storm's individual features change with time along the plane of the RHI vertical cross-section.
- 435 During the 31 January to 2 February 2021 storm, the KASPR scan strategy consisted of the following sequence that was repeated every 15 minutes: PPI at 15 ° elevation angle (50 seconds), set of 8 cross-band RHIs (6 minutes), vertically pointing mode (2 minutes), set of 8 cross-band RHIs (6 minutes). KASPR's mechanical antenna took a few seconds to reverse direction at the end of each RHI sweep. Each single RHI sweep took \sim 30 seconds (scan rate of 4-6 sec/deg) and can be considered to be similar to a snapshot.
- Below the cloud-top generating cells in first example at 1558 UTC 1 February 2021 (Fig. 18), the reflectivity enhancements bend with the wind patterns which switch direction several times through the depth of the echo. The spectrum width is enhanced at echo top associated with overturning circulations within the generating cells (Fig. 18a). Other narrow layers of enhanced spectrum width are present at several altitudes including close to the surface (Fig. 18a). The Doppler velocity field helps to illustrate the horizontal winds and how they vary with height (Fig. 18b). Near cloud top the winds are left to right, corresponding
- to a wind with a southerly component (wind coming from the south). In the layer between 2.3 and 3 km AGL the magnitude of the velocity is near zero which indicates the wind direction is pointing perpendicular to the radar beam. Between the surface and 1 km altitude there is shift in the wind direction to a wind with a North component illustrated by the change in sign of the Doppler velocity. The reflectivity field shows a lot of detail, including ice streamers that manifest from the overturning circulations near echo top (Fig. 18c). The ice streamer features become tilted and smeared on the way to the surface, likely
- 450 due to the distinct layers in the wind profile illustrated in the Doppler velocity field. In this example, the cross sections are plotted in a 1:1 aspect ratio so the tilt of the features is shown as it occurs in reality. As the snow particles within the enhanced reflectivity features descend in the storm they move much faster sideways than they do vertically. Unless the horizontal winds are very weak, snow cannot fall "straight" down in a column. It is also important to note that the precipitation particles are not all falling within the plane of the RHI. In particular, reflectivity values at altitudes with layers of near zero Doppler velocity are
- 455 potentially either moving in or out perpendicular to the cross-section. Whenever the wind direction changes between layers, the trajectories of individual precipitation particles turn with the wind, yielding complex 3D trajectories between their origin near cloud top and the surface.

In the second example a few hours later at 1928 UTC (Fig. 19), the cloud-top generating cells are still evident and the bending of the enhancements to the left then the right is more evident. The echo is slightly shallower overall and the reflectivity

field is more variable near cloud top varying from close to minimum detectable echo at -5 dBZ to close to 25 dBZ (Fig. 460 19c). There is some locally higher spectral width and likely turbulence close to 5 km altitude near echo top at the location of generating cells near -24 to -26 km and directly above the radar near 0 km (Fig. 19a). There is a discontinuity in the direction of tilt of ice streamers within the reflectivity field at about 3 km altitude from toward the right (North) to toward the left (South) corresponding to the wind shift observed in the Doppler velocity field (Fig. 19b). Similar to at 1558 UTC, the wind also sharply shifts direction to a North wind at about 1 km altitude above the surface.

465

470

The aircraft radar cross sections from the NASA IMPACTS campaign and RHI scans from the KASPR radar illustrate how features in the snow reflectivity field are tilted and smeared in winter storms. The lack of vertical column continuity of enhanced reflectivity aloft to the surface complicates the interpretation of reflectivity from PPI scanning radar in snow and provides a physical explanation for why we are not seeing a strong relationship between enhanced reflectivity aloft and snow rates at the surface.

4 Conclusions

Where and when heavy snow is likely to occur in northeast US winter storms is both a high impact and thorny problem. We analyzed observations of a large sample of snow storm events with negligible orographic forcing in the northeast US to improve the understanding of how hourly snowfall rates relate to structural characteristics of these winter storms. Data are from 264

- storm days over 11 years (2012-2023) which yielded over 7500 time-spatial matched pairs of hourly surface observations and 475 radar data that included enhanced reflectivity features in snow. Motivated by previous work, we examined mesoscale snow bands (locally-enhanced reflectivity features) - a "prime suspect" in the occurrence of heavy snowfall. Most of the time in northeast US winter storms, the snow rates are low (75% of hours had liquid equivalent snow rates less than 1 mm hr^{-1} [horizontal annotations on light blue bars in Fig. 8c, d]) and only 4% of hours had heavy snow rates > 2.5 mm hr⁻¹ (Fig.
- 8). Our data set excludes conditions with high surface winds (> 5 m s⁻¹) so these data are representative of non-blizzard 480 conditions. Consistent with previous work, higher snow rates are more likely to occur closer to the low-pressure center (within 250-500 km), especially in the northwest and northeast quadrants of the storm (Fig. 7).

Regional radar mosaics over the northeast US were created from the NWS NEXRAD network that included output from two new objective image processing methods developed specifically for this work: the removal of mixed precipitation areas (Tomkins et al., 2022), and the objective identification of locally-enhanced reflectivity features in snow (Tomkins et al.,

485 2024). Potential associations between radar reflectivity structures in the vicinity of ASOS stations and hourly snow rates were examined in terms of incidence of locally-enhanced reflectivity features as well as all snow echo.

Evidence from our analysis demonstrates that operational PPI scanning radar observed locally-enhanced reflectivity features within these snow storms are not consistently associated with heavy snowfall rates at the surface. When enhanced reflectivity features pass over over a location (area \times time fractions > 0.5), only 1 out of 4 occurrences have hourly heavy surface snow 490

liquid water equivalents ($\geq 2.5 \text{ mm hr}^{-1}$) (Fig. 8a, c). Evidence from fine spatial resolution vertical cross-sections obtained in 57 airborne radar transects by the NASA ER-2 aircraft during the IMPACTS field campaign, and from the ground-based Stony Brook University KASPR scanning fast update RHIs shows why the association between snow bands and surface snow rates is weak. Simply put, snow particles rarely fall straight down (Figs. 13-19). Locally enhanced reflectivity features in snow

- 495 are typically *tilted and smeared* as the precipitation-size ice is blown sideways by the horizontal wind for 10s of kilometers. Precipitation-size ice has typical fall speeds of $1 \text{ m s}^{-1} \pm 0.5 \text{ m s}^{-1}$ (Fitch et al., 2021). It takes an ice particle 16.6 minutes to descend 1 km if it is falling at 1 m s^{-1} . In that time, it will move laterally 10 km in a horizontal wind of 10 m s^{-1} . In comparison, a rain drop falling at 5 m s^{-1} will only take 3.3 minutes to descend 1 km, and would move laterally only 2 km in a horizontal wind of 10 m s^{-1} .
- 500 Numerous previous studies of radar observations going back to the 1950's Marshall (1953) have shown that ice streamers are tilted as they are blown side ways with the horizontal wind. The crucial nuance revealed by the analysis of large sample sizes in our study is that the extent of the smearing during that process usually yields few situations where the locally higher reflectivity aloft results in high snowfall rates at the surface. A set of snow particles in a volume at 2 km altitude are unlikely to all arrive together at the surface because of variations in their fall speeds and small scale variations in the horizontal wind
- 505 including turbulence. An additional factor complicating interpretation of enhanced radar reflectivity in snow is that it does not always imply increased ice mass (i.e. aggregation, Table 1). Our work suggests that it is more useful to focus on the duration of snow radar echo over a given location to predict higher snowfall accumulations rather than focus on the locally-enhanced reflectivity features.
- While case studies can be informative, those that focus on storms with heavy snowfall may not be representative of a 510 large sample of snow storms that include a range of storm intensities and durations. Primary bands are associated with strong frontogenesis and high snowfall accumulation but don't occur that often (Novak et al., 2004; Kenyon et al., 2020; Ganetis et al., 2018). Multi-bands occur more frequently but are found in environments with and without frontogenesis (Ganetis et al., 2018). Hence, in non-orographic storms, the presence of snow bands in radar reflectivity cannot be used as a proxy for sustained upward motions.
- 515 When students learn how to interpret radar reflectivity, the vast majority of examples used in training are from rain layers. The close association between locations with stronger reflectivities several kilometers above the surface and higher surface precipitation rates while appropriate for rain is not for snow. Practitioners and automated systems interpreting observed radar data would benefit from utilizing different "rules of thumb" for rain versus snow.

Code and data availability. Data: The NWS NEXRAD Level-II data used in Figs. 2, 4, 5, 13, 14, 15, 16, and 17 can be accessed from the
 National Centers for Environmental Information (NCEI) at https://www.ncei.noaa.gov/products/radar/next-generation-weather-radar. The
 radar composites created from the NEXRAD Level-II data used in Figs. 2, 4, 5, 13, 14, 15, 16, and 17 can be accessed from a Dryad
 repository at https://doi.org/10.5061/dryad.rbnzs7hj9. The NWS ASOS data used in Figs. 2.1.1, 7, 5, 9, 10, 11, 12 can be accessed from
 NCEI at https://www.ncei.noaa.gov/products/land-based-station/automated-surface-weather-observing-systems. The ERA5 data used to cre-

ate the low pressure tracks in Fig. 6 can be accessed from the Copernicus Climate Data Store at https://cds.climate.copernicus.eu/datasets/

525 reanalysis-era5-single-levels?tab=overview. The derived low pressure tracks created from the ERA5 data can be accessed from an OSF directory at https://osf.io/az5w2/. The ER-2 radar data used in Figs. 13–17 can be accessed from NASA at https://ghrc.nsstc.nasa.gov/uso/ ds_details/collections/impactsC.html.

Code: The functions used to create the feature detection fields are available in Py-ART (Helmus and Collis, 2016) and be accessed via https://arm-doe.github.io/pyart/API/generated/pyart.retrieve.feature_detection.html. An example of how to use the function is provided here: https://arm-doe.github.io/pyart/examples/retrieve/plot_feature_detection.html.

Video supplement. List of animations with captions and filenames

530

All animations can be viewed at: https://doi.org/10.5446/s_1851. Individual animations can be viewed by following the DOI URL.

Animation-Figure-9: Animated plot of Fig. 9 showing an example when a heavy snow rate (≥ 2.5 mm hr⁻¹) and high
feature area × time fraction (> 0.5) are observed over an hour. (Top panel) Feature detection field from NEXRAD regional mosaic animated over 16 December 20:00 UTC to 17 December 20:00 UTC with Albany, NY ASOS station (KALB) and 25 km radius annotated in purple and (bottom panel) time series of hourly precipitation rate between 16 December 20:00 UTC and 17 December 20:00 UTC from KALB (blue annotations) and area of each feature category within 25 km of KALB (yellow: strong area, orange: faint area, and teal: background area). In the bottom panel, purple vertical line indicates time of specific NEXRAD regional mosaic in the top panel.

Title: 17 December 2020 area × time fraction example DOI: https://doi.org/10.5446/69385

Animation-Figure-10: Animated plot of Fig. 10 showing an example when a low/moderate snow rate (< 2.5 mm hr⁻¹) and high feature area × time fraction (> 0.5) are observed over an hour. (Top panel) Feature detection field from NEXRAD regional mosaic animated over 26 January 12:00 UTC to 27 January 00:00 UTC with Providence, RI ASOS station (KPVD) and 25 km radius annotated in purple and (bottom panel) time series of hourly precipitation rate between 26 January 12:00 UTC and 27 January 00:00 UTC from KPVD (blue annotations) and area of each feature category within 25 km of KPVD (yellow: strong area, orange: faint area, and teal: background area). In the bottom panel, purple vertical line indicates time of specific NEXRAD regional mosaic in the top panel.

Title: 26 January 2021 area × time fraction example DOI: https://doi.org/10.5446/69386

Animation-Figure-11: Animated plot of Fig. 11 showing an example when a low/moderate snow rate (< 2.5 mm hr⁻¹) and low feature area × time fraction (≤ 0.5) are observed over an hour. (Top panel) Feature detection field from NEXRAD regional mosaic animated over 02 February 00:00 UTC to 03 February 00:00 UTC with Lebanon, NH ASOS station (KLEB) and 25 km radius annotated in purple and (bottom panel) time series of hourly precipitation rate between 02 February 00:00 UTC and 03 February 00:00 UTC from KLEB (blue annotations) and area of each feature category within 25 km of KLEB

(yellow: strong area, orange: faint area, and teal: background area). In the bottom panel, purple vertical line indicates time of 555 specific NEXRAD regional mosaic in the top panel.

Title: 02 February 2021 area × time fraction example DOI: https://doi.org/10.5446/69387

Animation-Figure-12: Animated plot of Fig. 12 showing an example when a heavy snow rate (> 2.5 mm hr⁻¹) and low feature area \times time fraction (< 0.5) are observed over an hour. (Top panel) Feature detection field from NEXRAD regional mosaic animated over 27 January 00:00 UTC to 27 January 18:00 UTC with Worcester, MA ASOS station (KORH) and 25 km 560 radius annotated in purple and (bottom panel) time series of hourly precipitation rate between 27 January 00:00 UTC and 27 January 18:00 UTC from KORH (blue annotations) and area of each feature category within 25 km of KORH (yellow: strong area, orange: faint area, and teal: background area). In the bottom panel, purple vertical line indicates time of specific NEXRAD regional mosaic in the top panel.

565

Title: 27 January 2021 area × time fraction example DOI: https://doi.org/10.5446/69388

Animation-Figure-13: An animation of a flight leg from 05 February 2020 between 21:11:29 and 21:31:09 UTC (the flight leg before the one shown in Fig. 13). (Left panel) Image muted reflectivity from NEXRAD radar mosaic, green line indicates path of ER-2 flight. Right panels are reflectivity fields from the radars on the ER-2, wavelength decreases from top to bottom. Vertical line in right panels indicates location of ER-2 path and small x marks the height of the radar beam in the NEXRAD mosaic.

570

585

Title: 05 February 2020 NEXRAD & EXRAD animation DOI: https://doi.org/10.5446/69554

Animation-Figure-18: Animated plot of Fig. 18 showing (a) Spectrum Width $[m s^{-1}]$, (b) Doppler Velocity $[m s^{-1}]$, and (c) Reflectivity [dBZ] RHIs from KaSPR radar at Stony Brook University between 15:00 and 17:00 UTC on 1 February 2021. RHIs are scanned up and over the radar (at 0 km on x-axis). Radar beam is partially blocked near edge of scan on right side.

```
Plotted in a 1:1 aspect ratio.
575
```

Title: 01 February 2021 KaSPR RHI example 1 DOI: https://doi.org/10.5446/69389

Animation-Figure-19: Animated plot of Fig. 19 showing (a) Spectrum Width $[m s^{-1}]$, (b) Doppler Velocity $[m s^{-1}]$, and (c) Reflectivity [dBZ] RHIs from the KaSPR radar at Stony Brook University at between 18:30 and 20:30 UTC on 1 February 2021. The RHIs are scanned up and over the radar (at 0 km on x-axis). Radar beam is partially blocked near edge of scan on right side. Plotted in a 1:1 aspect ratio.

Title: 01 February 2021 KaSPR RHI example 2 DOI: https://doi.org/10.5446/69391

Animation-Figure-19-19-full: Animated plot of full event from Fig. 18 and 19 showing (a) Spectrum Width $[m s^{-1}]$, (b) Doppler Velocity [m s⁻¹], and (c) Reflectivity [dBZ] RHIs from the KaSPR radar at Stony Brook University between 10:00 UTC on 31 January 2021 and 11:00 UTC on 2 February 2021. The RHIs are scanned up and over the radar (at 0 km on x-axis). Radar beam is partially blocked near edge of scan on right side. Plotted in a 1:1 aspect ratio.

⁵⁸⁰

Author contributions. LMT and SEY conceptualized the project and designed the methodology with input from MAM. LMT wrote the Python software with input from SEY and MAM. MO curated the KaSPR data and CNH curated the NASA IMPACTS EXRAD VAD data. LMT prepared the manuscript and the figures. All authors contributed to editing and review.

590 Competing interests. The authors declare that they have no conflict of interest.

Acknowledgements. The authors thank Kevin Burris and Luke Allen for their helpful feedback and support throughout the entirety of this project. Brian Colle, Matthew Parker, and L. Baker Perry provided insightful feedback on the analysis and methodology. Anya Aponte-Torres, Declan Crowe, Jordan Fritz, Cameron Gilbert, Wayne Johnson, Rebecca Moore, McKenzie Peters, and McKenzie Sevier assisted with data processing. Jordan Fritz and Rebecca Moore produced and compiled the ER-2 flight leg plots for the supplemental material. The authors also express their sincere appreciation to the entire the NASA IMPACTS project team. This paper greatly benefited from the data collected during 3 seasons of research aircraft deployments and the insightful conversations with science team members. This research has been supported by the National Science Foundation (AGS-1905736), the National Aeronautics and Space Administration (80NSSC19K0354), and the Center

for Geospatial Analytics at North Carolina State University.

References

630

- 600 Ansari, S., Greco, S. D., Kearns, E., Brown, O., Wilkins, S., Ramamurthy, M., Weber, J., May, R., Sundwall, J., Layton, J., Gold, A., Pasch, A., and Lakshmanan, V.: Unlocking the Potential of NEXRAD Data through NOAA's Big Data Partnership, Bulletin of the American Meteorological Society, 99, 189–204, https://doi.org/10.1175/BAMS-D-16-0021.1, 2018.
 - Baxter, M. A. and Schumacher, P. N.: Distribution of Single-Banded Snowfall in Central U.S. Cyclones, Weather and Forecasting, 32, 533–554, https://doi.org/10.1175/WAF-D-16-0154.1, 2017.
- 605 Bentley, A. M., Bosart, L. F., and Keyser, D.: A Climatology of Extratropical Cyclones Leading to Extreme Weather Events over Central and Eastern North America, Monthly Weather Review, 147, 1471–1490, https://doi.org/10.1175/MWR-D-18-0453.1, 2019.

Bruce, J. P. and Clark, R. H.: Introduction to Hydrometeorology, Pergamon Press Ltd., London, 1966.

Clark, J. H. E., James, R. P., and Grumm, R. H.: A Reexamination of the Mechanisms Responsible for Banded Precipitation, Monthly Weather Review, 130, 3074–3086, https://doi.org/10.1175/1520-0493(2002)130<3074:AROTMR>2.0.CO;2, 2002.

610 Colle, B. A., Stark, D., and Yuter, S. E.: Surface Microphysical Observations within East Coast Winter Storms on Long Island, New York, Monthly Weather Review, 142, 3126–3146, https://doi.org/10.1175/MWR-D-14-00035.1, 2014.

Colle, B. A., Yeh, P., Finlon, J. A., McMurdie, L., McDonald, V., and DeLaFrance, A.: An Investigation of a Northeast U.S. Cyclone Event Without Well-Defined Snow Banding During IMPACTS, Monthly Weather Review, -1, https://doi.org/10.1175/MWR-D-22-0296.1, 2023.

Connelly, R. and Colle, B. A.: Validation of Snow Multibands in the Comma Head of an Extratropical Cyclone Using a 40-Member Ensemble,

615 Weather and Forecasting, 34, 1343–1363, https://doi.org/10.1175/WAF-D-18-0182.1, 2019.

Crawford, A. D., Schreiber, E. A. P., Sommer, N., Serreze, M. C., Stroeve, J. C., and Barber, D. G.: Sensitivity of Northern Hemisphere Cyclone Detection and Tracking Results to Fine Spatial and Temporal Resolution Using ERA5, Monthly Weather Review, 149, 2581– 2598, https://doi.org/10.1175/MWR-D-20-0417.1, 2021.

Cressman, G. P.: An Operational Objective Analysis System, Monthly Weather Review, 87, 367–374, https://doi.org/10.1175/1520-0493(1959)087<0367:AOOAS>2.0.CO;2, 1959.

Fenneman, N. M.: Physiographic divisions of the United States, Annals of the Association of American Geographers, 18, 261–353, 1928.
Fitch, K. E., Hang, C., Talaei, A., and Garrett, T. J.: Arctic observations and numerical simulations of surface wind effects on Multi-Angle Snowflake Camera measurements, Atmospheric Measurement Techniques, 14, 1127–1142, https://doi.org/10.5194/amt-14-1127-2021, 2021.

- 625 Fujiyoshi, Y., Endoh, T., Yamada, T., Tsuboki, K., Tachibana, Y., and Wakahama, G.: Determination of a Z-R Relationship for Snowfall Using a Radar and High Sensitivity Snow Gauges, Journal of Applied Meteorology and Climatology, 29, 147–152, https://doi.org/10.1175/1520-0450(1990)029<0147:DOARFS>2.0.CO;2, 1990.
 - Fujiyoshi, Y., Yoshimoto, N., and Takeda, T.: A dual-Doppler radar study of longitudinal-mode snowbands. Part I: A three-dimensional kinematic structure of meso-γ-scale convective cloud systems within a longitudinal-mode snowband, Monthly weather review, 126, 72–91, 1998.
 - Ganetis, S. A. and Colle, B. A.: The Thermodynamic and Microphysical Evolution of an Intense Snowband during the Northeast U.S. Blizzard of 8–9 February 2013, Monthly Weather Review, 143, 4104–4125, https://doi.org/10.1175/MWR-D-14-00407.1, 2015.
 - Ganetis, S. A., Colle, B. A., Yuter, S. E., and Hoban, N. P.: Environmental Conditions Associated with Observed Snowband Structures within Northeast U.S. Winter Storms, Monthly Weather Review, 146, 3675–3690, https://doi.org/10.1175/MWR-D-18-0054.1, 2018.
- Groisman, P. Y. and Legates, D. R.: The accuracy of United States precipitation data, Bull. Amer. Meteor Soc., 75, 215–227, 1994.

- Guarino, J. and Firestine, T.: Effects of the February 2010 Snowstorms on Airline Performance, Tech. Rep. SR-019, US Department of Transportation, https://doi.org/10.21949/1501623, 2010.
- Han, M., Rauber, R. M., Ramamurthy, M. K., Jewett, B. F., and Grim, J. A.: Mesoscale Dynamics of the Trowal and Warm-Frontal Regions of Two Continental Winter Cyclones, Monthly Weather Review, 135, 1647–1670, https://doi.org/10.1175/MWR3377.1, 2007.
- 640 Helms, C. N., Walker McLinden, M. L., Heymsfield, G. M., and Guimond, S. R.: Reducing Errors in Velocity–Azimuth Display (VAD) Wind and Deformation Retrievals from Airborne Doppler Radars in Convective Environments, Journal of Atmospheric and Oceanic Technology, 37, 2251–2266, https://doi.org/10.1175/JTECH-D-20-0034.1, 2020.
 - Helmus, J. J. and Collis, S. M.: The Python ARM Radar Toolkit (Py-ART), a Library for Working with Weather Radar Data in the Python Programming Language, Journal of Open Research Software, 4, https://doi.org/10.5334/jors.119, 2016.
- Hersbach, H., Bell, B., Berrisford, P., Hirahara, S., Horányi, A., Muñoz-Sabater, J., Nicolas, J., Peubey, C., Radu, R., Schepers, D., Simmons, A., Soci, C., Abdalla, S., Abellan, X., Balsamo, G., Bechtold, P., Biavati, G., Bidlot, J., Bonavita, M., De Chiara, G., Dahlgren, P., Dee, D., Diamantakis, M., Dragani, R., Flemming, J., Forbes, R., Fuentes, M., Geer, A., Haimberger, L., Healy, S., Hogan, R. J., Hólm, E., Janisková, M., Keeley, S., Laloyaux, P., Lopez, P., Lupu, C., Radnoti, G., de Rosnay, P., Rozum, I., Vamborg, F., Villaume, S., and Thépaut, J.-N.: The ERA5 Global Reanalysis, Quarterly Journal of the Royal Meteorological Society, 146, 1999–2049,
- 650 https://doi.org/10.1002/qj.3803, 2020.
 - Heymsfield, G. M., Bidwell, S. W., Caylor, I. J., Ameen, S., Nicholson, S., Boncyk, W., Miller, L., Vandemark, D., Racette, P. E., and Dod, L. R.: The EDOP Radar System on the High-Altitude NASA ER-2 Aircraft, Journal of Atmospheric and Oceanic Technology, 13, 795–809, 1996.
 - Hoban, N. P.: Observed Characteristics of Mesoscale Banding in Coastal Northeast U.S. Snow Storms, M.S. Thesis, North Carolina State
- 655 University, 2016.
 - Kenyon, J. S., Keyser, D., Bosart, L. F., and Evans, M. S.: The Motion of Mesoscale Snowbands in Northeast U.S. Winter Storms, Weather and Forecasting, 35, 83–105, https://doi.org/10.1175/WAF-D-19-0038.1, 2020.
 - Kochendorfer, J., Earle, M., Rasmussen, R., Smith, C., Yang, D., Morin, S., Mekis, E., Buisan, S., Roulet, Y.-A., Landolt, S., et al.: How well are we measuring snow post-SPICE?, Bulletin of the American Meteorological Society, 103, E370–E388, 2022.
- 660 Kocin, P. J. and Uccellini, L. W.: Northeast Snowstorms., vol. 1, Meteorological Monographs, 2004.
 - Kosiba, K. A., Wurman, J., Knupp, K., Pennington, K., and Robinson, P.: Ontario Winter Lake-effect Systems (OWLeS): Bulk characteristics and kinematic evolution of misovortices in long-lake-axis-parallel snowbands, Monthly Weather Review, 148, 131–157, 2019.
- Krajewski, W. F., Morrissey, M. L., Smith, J. A., and Rexroth, D. T.: The Accuracy of the Area-Threshold Method: A Model-based Simulation Study, Journal of Applied Meteorology and Climatology, 31, 1396–1406, https://doi.org/10.1175/1520-0450(1992)031<1396:TAOTAT>2.0.CO;2, 1992.
- Kristovich, D. A., Clark, R. D., Frame, J., Geerts, B., Knupp, K. R., Kosiba, K. A., Laird, N. F., Metz, N. D., Minder, J. R., Sikora, T. D., et al.:
 - The Ontario winter lake-effect systems field campaign: Scientific and educational adventures to further our knowledge and prediction of lake-effect storms, Bulletin of the American Meteorological Society, 98, 315–332, 2017.
- Lackmann, G. M. and Thompson, G.: Hydrometeor Lofting and Mesoscale Snowbands, Monthly Weather Review, 147, 3879–3899,
 https://doi.org/10.1175/MWR-D-19-0036.1, 2019.
 - Leonardo, N. M. and Colle, B. A.: Analysis of Snow Multibands and Their Environments with High-Resolution Idealized Simulations, Monthly Weather Review, 152, 925–943, https://doi.org/10.1175/MWR-D-23-0211.1, 2024.

- Li, L., Heymsfield, G., Carswell, J., Schaubert, D. H., McLinden, M. L., Creticos, J., Perrine, M., Coon, M., Cervantes, J. I., Vega, M., Guimond, S., Tian, L., and Emory, A.: The NASA High-Altitude Imaging Wind and Rain Airborne Profiler, IEEE Transactions on Geoscience and Remote Sensing, 54, 298–310, https://doi.org/10.1109/TGRS.2015.2456501, 2016.
- Marshall, J. S.: PRECIPITATION TRAJECTORIES AND PATTERNS, Journal of the Atmospheric Sciences, 10, 25–29, https://doi.org/10.1175/1520-0469(1953)010<0025:PTAP>2.0.CO;2, publisher: American Meteorological Society Section: Journal of the Atmospheric Sciences, 1953.
 - Martinaitis, S. M., Cocks, S. B., Qi, Y., Kaney, B. T., Zhang, J., and Howard, K.: Understanding Winter Precipitation Impacts on Auto-
- 680 mated Gauge Observations within a Real-Time System, Journal of Hydrometeorology, 16, 2345–2363, https://doi.org/10.1175/JHM-D-15-0020.1, 2015.
 - Matrosov, S. Y., Shupe, M. D., and Djalalova, I. V.: Snowfall retrievals using millimeter-wavelength cloud radars, Journal of Applied Meteorology and Climatology, 47, 769–777, 2008.
- Mazon, J., Niemelä, S., Pino, D., Savijärvi, H., and Vihma, T.: Snow bands over the Gulf of Finland in wintertime, Tellus A: Dynamic
 Meteorology and Oceanography, 67, 25 102, 2015.
 - McLinden, M. L. W., Li, L., Heymsfield, G. M., Coon, M., and Emory, A.: The NASA GSFC 94-GHz Airborne Solid-State Cloud Radar System (CRS), Journal of Atmospheric and Oceanic Technology, 38, 1001–1017, https://doi.org/10.1175/JTECH-D-20-0127.1, 2021.
 - McMurdie, L. A., Heymsfield, G. M., Yorks, J. E., Braun, S. A., Skofronick-Jackson, G., Rauber, R. M., Yuter, S., Colle, B., McFarquhar, G. M., Poellot, M., Novak, D. R., Lang, T. J., Kroodsma, R., McLinden, M., Oue, M., Kollias, P., Kumjian, M. R., Greybush, S. J., Heyms-
- 690 field, A. J., Finlon, J. A., McDonald, V. L., and Nicholls, S.: Chasing Snowstorms: The Investigation of Microphysics and Precipitation for Atlantic Coast-Threatening Snowstorms (IMPACTS) Campaign, Bulletin of the American Meteorological Society, 103, E1243–E1269, https://doi.org/10.1175/BAMS-D-20-0246.1, 2022.
 - Menne, M. J., Durre, I., Vose, R. S., Gleason, B. E., and Houston, T. G.: An Overview of the Global Historical Climatology Network-Daily Database, Journal of Atmospheric and Oceanic Technology, 29, 897–910, https://doi.org/10.1175/JTECH-D-11-00103.1, 2012.
- 695 Mitchell, D. L., Zhang, R., and Pitter, R. L.: Mass-dimensional relationships for ice particles and the influence of riming on snowfall rates, Journal of Applied Meteorology and Climatology, 29, 153–163, 1990.
 - Mulholland, J. P., Frame, J., Nesbitt, S. W., Steiger, S. M., Kosiba, K. A., and Wurman, J.: Observations of misovortices within a long-lakeaxis-parallel lake-effect snowband during the OWLeS project, Monthly Weather Review, 145, 3265–3291, 2017.

Murakami, M.: Inner structures of snow clouds over the Sea of Japan observed by instrumented aircraft: A review, Journal of the Meteoro-

700 logical Society of Japan. Ser. II, 97, 5–38, 2019.

- Nicosia, D. J. and Grumm, R. H.: Mesoscale Band Formation in Three Major Northeastern United States Snowstorms, Weather and Forecasting, 14, 346–368, https://doi.org/10.1175/1520-0434(1999)014<0346:MBFITM>2.0.CO;2, 1999.
 - Norris, J., Vaughan, G., and Schultz, D. M.: Snowbands over the English Channel and Irish Sea during cold-air outbreaks, Quarterly Journal of the Royal Meteorological Society, 139, 1747–1761, 2013.
- 705 Novak, D. R. and Colle, B. A.: Diagnosing Snowband Predictability Using a Multimodel Ensemble System, Weather and Forecasting, 27, 565–585, https://doi.org/10.1175/WAF-D-11-00047.1, 2012.
 - Novak, D. R., Bosart, L. F., Keyser, D., and Waldstreicher, J. S.: An Observational Study of Cold Season–Banded Precipitation in Northeast U.S. Cyclones, Weather and Forecasting, 19, 993–1010, https://doi.org/10.1175/815.1, 2004.

Novak, D. R., Colle, B. A., and Yuter, S. E.: High-Resolution Observations and Model Simulations of the Life Cycle of an Intense Mesoscale

- 710 Snowband over the Northeastern United States, Monthly Weather Review, 136, 1433–1456, https://doi.org/10.1175/2007MWR2233.1, 2008.
 - Novak, D. R., Colle, B. A., and McTaggart-Cowan, R.: The Role of Moist Processes in the Formation and Evolution of Mesoscale Snowbands within the Comma Head of Northeast U.S. Cyclones, Monthly Weather Review, 137, 2662–2686, https://doi.org/10.1175/2009MWR2874.1, 2009.
- 715 Novak, D. R., Colle, B. A., and Aiyyer, A. R.: Evolution of Mesoscale Precipitation Band Environments within the Comma Head of Northeast U.S. Cyclones, Monthly Weather Review, 138, 2354–2374, https://doi.org/10.1175/2010MWR3219.1, 2010.
 - Novak, D. R., Perfater, S. E., Demuth, J. L., Bieda, S. W., Carbin, G., Craven, J., Erickson, M. J., Jeglum, M. E., Kastman, J., Nelson, J. A., Rudack, D. E., Staudenmaier, M. J., and Waldstreicher, J. S.: Innovations in Winter Storm Forecasting and Decision Support Services, Bulletin of the American Meteorological Society, 104, E715–E735, https://doi.org/10.1175/BAMS-D-22-0065.1, 2023.
- 720 Oue, M., Kollias, P., Luke, E. P., and Mead, J.: A New Ka-Band Scanning Radar Facility: Polarimetric and Doppler Spectra Measurements of Snow Events, AGU Fall Meeting Abstracts, A31G-2270, 2017.
 - Oue, M., Colle, B. A., Yuter, S. E., Kollias, P., Yeh, P., and Tomkins, L. M.: Microscale Updrafts Within Northeast U.S. Coastal Snowstorms Using High-Resolution Cloud Radar Measurements, Monthly Weather Review, -1, https://doi.org/10.1175/MWR-D-23-0055.1, 2024.

Picca, J. C., Schultz, D. M., Colle, B. A., Ganetis, S., Novak, D. R., and Sienkiewicz, M. J.: The Value of Dual-Polarization Radar in

- 725 Diagnosing the Complex Microphysical Evolution of an Intense Snowband, Bulletin of the American Meteorological Society, 95, 1825– 1834, https://doi.org/10.1175/BAMS-D-13-00258.1, 2014.
 - Radford, J. T., Lackmann, G. M., Goodwin, J., Correia Jr, J., and Harnos, K.: An iterative approach toward development of ensemble visualization techniques for high-impact winter weather hazards: Part I: Product development, Bulletin of the American Meteorological Society, 104, E1630–E1648, 2023.
- 730 Rasmussen, R., Dixon, M., Hage, F., Cole, J., Wade, C., Tuttle, J., McGettigan, S., Carty, T., Stevenson, L., Fellner, W., Knight, S., Karplus, E., and Rehak, N.: Weather Support to Deicing Decision Making (WSDDM): A Winter Weather Nowcasting System, Bulletin of the American Meteorological Society, 82, 579–596, https://doi.org/10.1175/1520-0477(2001)082<0579:WSTDDM>2.3.CO;2, 2001.
 - Rasmussen, R., Dixon, M., Vasiloff, S., Hage, F., Knight, S., Vivekanandan, J., and Xu, M.: Snow Nowcasting Using a Real-Time Correlation of Radar Reflectivity with Snow Gauge Accumulation, Journal of Applied Meteorology and Climatology, 42, 20–36, https://doi.org/10.1175/1520-0450(2003)042<0020:SNUART>2.0.CO:2, 2003.
- Rasmussen, R., Baker, B., Kochendorfer, J., Meyers, T., Landolt, S., Fischer, A. P., Black, J., Thériault, J. M., Kucera, P., Gochis, D., Smith, C., Nitu, R., Hall, M., Ikeda, K., and Gutmann, E.: How Well Are We Measuring Snow: The NOAA/FAA/NCAR Winter Precipitation Test Bed, Bulletin of the American Meteorological Society, 93, 811–829, https://doi.org/10.1175/BAMS-D-11-00052.1, 2012.

Rauber, R. M. and Nesbitt, S. W.: Radar Meteorology: A First Course, John Wiley & Sons, 2018.

- 740 Sato, K., Kameda, T., and Shirakawa, T.: Heavy snowfall at Iwamizawa influenced by the Tsushima warm current, Journal of the Meteorological Society of Japan. Ser. II, 100, 873–891, 2022.
 - Shields, M. T., Rauber, R. M., and Ramamurthy, M. K.: Dynamical Forcing and Mesoscale Organization of Precipitation Bands in a Midwest Winter Cyclonic Storm, Monthly Weather Review, 119, 936–964, https://doi.org/10.1175/1520-0493(1991)119<0936:DFAMOO>2.0.CO;2, 1991.

- 745 Smith, T. M., Lakshmanan, V., Stumpf, G. J., Ortega, K. L., Hondl, K., Cooper, K., Calhoun, K. M., Kingfield, D. M., Manross, K. L., Toomey, R., et al.: Multi-Radar Multi-Sensor (MRMS) severe weather and aviation products: Initial operating capabilities, Bulletin of the American Meteorological Society, 97, 1617–1630, https://doi.org/10.1175/BAMS-D-14-00173.1, 2016.
 - Stark, D., Colle, B. A., and Yuter, S. E.: Observed Microphysical Evolution for Two East Coast Winter Storms and the Associated Snow Bands, Monthly Weather Review, 141, 2037–2057, https://doi.org/10.1175/MWR-D-12-00276.1, 2013.
- 750 Tessendorf, S. A., French, J. R., Friedrich, K., Geerts, B., Rauber, R. M., Rasmussen, R. M., Xue, L., Ikeda, K., Blestrud, D. R., Kunkel, M. L., Parkinson, S., Snider, J. R., Aikins, J., Faber, S., Majewski, A., Grasmick, C., Bergmaier, P. T., Janiszeski, A., Springer, A., Weeks, C., Serke, D. J., and Bruintjes, R.: A Transformational Approach to Winter Orographic Weather Modification Research: The SNOWIE Project, Bulletin of the American Meteorological Society, 100, 71–92, https://doi.org/10.1175/BAMS-D-17-0152.1, 2019.
- Tomkins, L. M.: Synthesis of Radar-Observed Characteristics, Storm Structures, and Surface Snowfall Rates in 10+ Years of Northeast US Winter Storms, Ph.D. thesis, North Carolina State University, 2024.
 - Tomkins, L. M., Yuter, S. E., Miller, M. A., and Allen, L. R.: Image Muting of Mixed Precipitation to Improve Identification of Regions of Heavy Snow in Radar Data, Atmospheric Measurement Techniques, 15, 5515–5525, https://doi.org/10.5194/amt-15-5515-2022, 2022.
 - Tomkins, L. M., Yuter, S. E., and Miller, M. A.: Dual adaptive differential threshold method for automated detection of faint and strong echo features in radar observations of winter storms, Atmospheric Measurement Techniques, 17, 3377–3399, https://doi.org/10.5194/amt-17-3377-2024, 2024.
 - Varcie, M. M., Zaremba, T. J., Rauber, R. M., McFarquhar, G. M., Finlon, J. A., McMurdie, L. A., Ryzhkov, A., Schnaiter, M., Järvinen, E., Waitz, F., Delene, D. J., Poellot, M. R., McLinden, M. L. W., and Janiszeski, A.: Precipitation Growth Processes in the Comma-Head Region of the 7 February 2020 Northeast Snowstorm: Results from IMPACTS, Journal of the Atmospheric Sciences, 80, 3–29, https://doi.org/10.1175/JAS-D-22-0118.1, 2022.
- 765 von Lerber, A., Moisseev, D., Bliven, L. F., Petersen, W., Harri, A.-M., and Chandrasekar, V.: Microphysical properties of snow and their link to Z e–S relations during BAECC 2014, Journal of Applied Meteorology and Climatology, 56, 1561–1582, 2017.
 - Wen, Y., Kirstetter, P., Gourley, J., Hong, Y., Behrangi, A., and Flamig, Z.: Evaluation of MRMS snowfall products over the western United States, Journal of Hydrometeorology, 18, 1707–1713, 2017.

Wexler, R.: Radar analysis of precipitation streamers observed 25 February 1954, Journal of Atmospheric Sciences, 12, 391–393, 1955.

Wexler, R. and Atlas, D.: Precipitation generating cells, Journal of Atmospheric Sciences, 16, 327–332, 1959.

760

- Yeh, P. and Colle, B. A.: A Comparison of Approaches to Objectively Identify Precipitation Structures Within the Comma Head of Mid-Latitude Cyclones, Journal of Atmospheric and Oceanic Technology, 2025.
 - Yuter, S. E. and Houze, R. A.: Three-Dimensional Kinematic and Microphysical Evolution of Florida Cumulonimbus. Part II: Frequency Distributions of Vertical Velocity, Reflectivity, and Differential Reflectivity, Monthly Weather Review, 123, 1941–1963, https://doi.org/10.1175/1520-0493(1995)123<1941:TDKAME>2.0.CO;2, 1995.
- Zaremba, T. J., Rauber, R. M., Girolamo, L. D., Loveridge, J. R., and McFarquhar, G. M.: On the Radar Detection of Cloud Seeding Effects in Wintertime Orographic Cloud Systems, Journal of Applied Meteorology and Climatology, 63, 27–45, https://doi.org/10.1175/JAMC-D-22-0154.1, 2023.
 - Zaremba, T. J., Rauber, R. M., Heimes, K., Yorks, J. E., Finlon, J. A., Nicholls, S. D., Selmer, P., McMurdie, L. A., and McFarquhar, G. M.:
- 780 Cloud-Top Phase Characterization of Extratropical Cyclones over the Northeast and Midwest United States: Results from IMPACTS, Journal of the Atmospheric Sciences, 81, 341–361, https://doi.org/10.1175/JAS-D-23-0123.1, 2024.

Zhao, Y., Fu, L., Yang, C.-F., and Chen, X.-F.: Case study of a heavy snowstorm associated with an extratropical cyclone featuring a back-bent warm front structure, Atmosphere, 11, 1272, 2020.



Figure 1. Joint distribution based on over 100,000 coincident aircraft observations of 1 Hz Nevzorov probe Ice Water Content samples and Wyoming Cloud Radar reflectivities obtained in light snow by the University of Wyoming King Air during the SNOWIE project in the mountains of western Idaho. Reflectivity values at the aircraft flight level were calculated by linear interpolation between the first valid range gates above and below the aircraft. Adapted from Figure 6 in Zaremba et al. (2023).



Figure 2. (a) An example of the reflectivity mosaic from 27 December 2020 09:17 UTC. Black dashed circles indicate the 200 km extent from each radar used in the mosaics. Black dots indicate ASOS stations where hourly snow rate is used in the analysis. (b) map of ASOS stations where daily snowfall accumulation is used to define a winter storm in this analysis.



Figure 3. Example time series of liquid equivalent precipitation rate $[mm hr^{-1}]$ from the Boston, MA ASOS station (KBOS) from 7 February 2021 06:00 UTC to 8 February 2021 01:00 UTC. Precipitation rates are represented as a bar spanning the hour they were accumulated. Plus signs indicates times when the wind speed is > 5 m s⁻¹ and *T* indicates times when trace amounts of precipitation where observed.



Figure 4. Locally-enhanced reflectivity feature classification for the examples presented in Sec. 3.2.2 (Figs. 13–17). Each row shows a different example. (a)-(c) 5 February 2020 21:49:12 UTC, (d)-(f) 7 February 2020 14:12:26 UTC, (g)-(i) 23 January 2023 15:08:56 UTC, (j)-(l) 28 February 2023 13:30:27 UTC, (m)-(o) 17 February 2022 20:29:16. Left column shows step 1, the input radar reflectivity (dBZ). Middle column shows step 2, the reflectivity field rescaled to estimated snow rate [mm hr^{-1}]. Right column shows step 3, the feature classification into faint and strong local features and background values. Each field is imaged muted to reduce the visual prominence of melting and mixed precipitation (gray scale) following Tomkins et al. (2022). Green, red, and purple lines indicate NASA ER-2 flight paths and arrow heads indicate location of the aircraft at the time of each plot. The feature classification method is detailed in Tomkins et al. (2024).



Figure 5. Illustration of how areal radar data and point measurements of snowfall rates are combined. (a) Shows the snow rate field and (b) shows the feature detection field centered on Massachusetts for 7 February 2021 18:42 UTC. (c) The corresponding time series of ASOS hourly precipitation rate (left axis) valid from 7 February 2021 06 UTC to 08 February 2021 01 UTC and echo areas (right axis) calculated within 25 km of Boston, MA ASOS station (KBOS: red dot in (a) and purple dot in (b)). Lines in time series (c) correspond to background echo area (teal), strong area (yellow) and faint area (orange) within 25 km of the KBOS station (rings in (a) and (b)). Purple vertical line annotated on time series (c) indicates the time of the maps. (d) Several examples of echo coverage over a given time that would yield an area \times time fraction of 0.5.



Figure 6. Map of (a) all tracks of low pressure centers and (b) density of low pressure center locations for events between 2012-2023 for the region shown. Color shading indicates low pressure magnitude in hPa units.



Figure 7. Lagrangian low-centric framework plot of hourly liquid equivalent snowfall rates in units of $m s^{-1}$. The plot's center represents the tracked low pressure center and each point represents 1 hour of data from an ASOS station color-coded by the associated liquid equivalent snowfall rate. Points are plotted with partial transparency to avoid obscuration.



Figure 8. Joint distributions of number of hours for (a) all feature (faint + strong) area × time fraction and (b) all echo (background + faint features + strong features) area × time fraction versus liquid equivalent precipitation rate $[mm hr^{-1}]$ for snow observations. (c) Bar chart summarizing feature area × time fraction distribution in (a) and (d) bar chart summarizing echo area × time fraction distribution in (b). Light blue bars in (c, d) represent liquid equivalent precipitation rate $< 2.5 mm hr^{-1}$ and dark blue bars represent liquid equivalent precipitation rate $< 2.5 mm hr^{-1}$ and dark blue bars represent liquid equivalent precipitation rate $< 2.5 mm hr^{-1}$ and dark blue bars represent liquid equivalent precipitation rate $< 2.5 mm hr^{-1}$ are annotated with horizontal lines on light blue bars in (c, d). Area × time fractions calculated with a 25 km radius and observations are paired with a 0-hour lag. Zero feature area × time fraction observations in (a, c) are not shown. In (a, b) 0.5 area × time fraction is annotated with a vertical black dashed line and 2.5 mm hr⁻¹ is annotated with a horizontal black dashed line. Bold annotated numbers in (a, b) indicate number of hours in each quadrant and italicized numbers indicate percent of total observations in each quadrant. The feature area × time fraction in (a, c) has 7606 total hours compared to the all echo area × time fraction in (b, d) with 17242 hours. The difference relates to the exclusion of hours with zero feature area × time fraction in (a, c).



Figure 9. An example when a heavy snow rate ($\geq 2.5 \text{ mm hr}^{-1}$) and high feature area × time fraction (> 0.5) are observed over an hour. (a) Feature detection field from NEXRAD regional mosaic at 17 December 2020 04:38:12 UTC with Albany, NY ASOS station (KALB) and 25 km radius annotated in purple, (b) 2D distribution from Fig. 8a with the specific hourly observation (04:00-05:00 UTC) annotated with red plus sign, and (c) time series of hourly precipitation rate over the entire event (16 December 20:00 UTC to 17 December 20:00 UTC) from KALB (blue annotations) and area of each feature category within 25 km of KALB (yellow: strong area, orange: faint area, and teal: background area). In (a), gray colors indicate regions of partially-melted or mixed precipitation. In (c), purple vertical line indicates time of specific NEXRAD regional mosaic in (a) and red bar on x-axis indicates the hour of observation at the red plus sign in (b). An animated version of this figure is available in the Video Supplement Animation-Figure-9.



Figure 10. An example when a low/moderate snow rate (< 2.5 mm hr^{-1}) and high feature area × time fraction (> 0.5) are observed over an hour. (a) Feature detection field from NEXRAD regional mosaic at 26 January 2021 21:07:39 UTC with Providence, RI ASOS station (KPVD) and 25 km radius annotated in purple, (b) 2D distribution from Fig. 8a with the specific hourly observation (21:00-22:00 UTC) annotated with red plus sign, and (c) time series of hourly precipitation rate over the entire event (26 January 12:00 UTC to 27 January 00:00 UTC) from KPVD (blue annotations) and area of each feature category within 25 km of KPVD (yellow: strong area, orange: faint area, and teal: background area). In (a), gray colors indicate regions of partially-melted or mixed precipitation. In (c), purple vertical line indicates time of specific NEXRAD regional mosaic in (a) and red bar on x-axis indicates the hour of observation at the red plus sign in (b). An animated version of this figure is available in the Video Supplement Animation-Figure-10.



Figure 11. An example when a low/moderate snow rate (< 2.5 mm hr^{-1}) and low feature area × time fraction (≤ 0.5) are observed over an hour. (a) Feature detection field from NEXRAD regional mosaic at 02 February 2021 07:08:30 UTC with Lebanon, NH ASOS station (KLEB) and 25 km radius annotated in purple, (b) 2D distribution from Fig. 8a with the specific hourly observation (07:00-08:00 UTC) annotated with red plus sign, and (c) time series of hourly precipitation rate over the entire event (02 February 00:00 UTC to 03 February 00:00 UTC) from KLEB (blue annotations) and area of each feature category within 25 km of KLEB (yellow: strong area, orange: faint area, and teal: background area). In (a), gray colors indicate regions of partially-melted or mixed precipitation. In (c), purple vertical line indicates time of specific NEXRAD regional mosaic in (a) and red bar on x-axis indicates the hour of observation at the red plus sign in (b). An animated version of this figure is available in the Video Supplement Animation-Figure-11.


Figure 12. An example when a heavy snow rate ($\geq 2.5 \text{ mm hr}^{-1}$) and low feature area × time fraction (≤ 0.5) are observed over an hour. (a) Feature detection field from NEXRAD regional mosaic at 27 January 2021 08:51:40 UTC with Worcester, MA ASOS station (KORH) and 25 km radius annotated in purple, (b) 2D distribution from Fig. 8a with the specific hourly observation (08:00-09:00 UTC) annotated with red plus sign, and (c) time series of hourly precipitation rate over the entire event (27 January 00:00 UTC to 27 January 18:00 UTC) from KORH (blue annotations) and area of each feature category within 25 km of KORH (yellow: strong area, orange: faint area, and teal: background area). In (a), gray colors indicate regions of partially-melted or mixed precipitation. In (c), purple vertical line indicates time of specific NEXRAD regional mosaic in (a) and red bar on x-axis indicates the hour of observation at the red plus sign in (b). An animated version of this figure is available in the Video Supplement Animation-Figure-12.



Figure 13. Vertical cross-section from 5 February 2020 21:42:04 to 21:56:44 UTC of (a) reflectivity [dBZ] from NASA EXRAD radar (nadir beam) and VAD winds derived from EXRAD radar (scanning beam), (b) velocity $[m s^{-1}]$, and (c) spectrum width $[m s^{-1}]$ from NASA CRS cloud radar. All vertical cross-sections are plotted with a 3:1 aspect ratio. Triangle icons next to (c) illustrate a 45° angle in a 1:1 and 3:1 aspect ratio. (d) Corresponding NEXRAD regional map of image muted reflectivity [dBZ] with ER-2 flight path in green, arrowhead denotes direction and location of aircraft at time of region map. CFADs of (e) wind speed and (f) wind direction of VAD winds in (a). Wind direction CFAD indicates the direction the wind is coming from and is plotted in polar coordinates where the angle represents the direction and each radius represents the altitude (0 km at the center). Black arrow in (a) indicates the compass direction of the aircraft during the transect.



Figure 14. Vertical cross-section from 7 February 2020 14:11:20 to 14:29:00 UTC of (a) reflectivity [dBZ] from NASA EXRAD radar (nadir beam) and VAD winds derived from EXRAD radar (scanning beam), (b) velocity $[m s^{-1}]$, and (c) spectrum width $[m s^{-1}]$ from NASA CRS cloud radar. All vertical cross-sections are plotted with a 3:1 aspect ratio. Triangle icons next to (c) illustrate a 45° angle in a 1:1 and 3:1 aspect ratio. (d) Corresponding NEXRAD regional map of image muted reflectivity [dBZ] with ER-2 flight path in green, arrowhead denotes direction and location of aircraft at time of region map. CFADs of (e) wind speed and (f) wind direction of VAD winds in (a). Wind direction CFAD indicates the direction the wind is coming from and is plotted in polar coordinates where the angle represents the direction and each radius represents the altitude (0 km at the center). Black arrow in (a) indicates the compass direction of the aircraft during the transect.



Figure 15. Vertical cross-section from 23 January 2023 14:59:16 to 15:22:02 UTC of (a) reflectivity [dBZ] from NASA EXRAD radar (nadir beam) and VAD winds derived from EXRAD radar (scanning beam), (b) velocity $[m s^{-1}]$, and (c) spectrum width $[m s^{-1}]$ from NASA HIWRAP (Ka-band) radar. All vertical cross-sections are plotted with a 3:1 aspect ratio. Triangle icons next to (c) illustrate a 45° angle in a 1:1 and 3:1 aspect ratio. (d) Corresponding NEXRAD regional map of image muted reflectivity [dBZ] with ER-2 flight path in green, arrowhead denotes direction and location of aircraft at time of region map. CFADs of (e) wind speed and (f) wind direction of VAD winds in (a). Wind direction CFAD indicates the direction the wind is coming from and is plotted in polar coordinates where the angle represents the direction and each radius represents the altitude (0 km at the center).



Figure 16. Vertical cross-section from 28 February 2023 13:11:48 to 13:36:34 UTC of (a) reflectivity [dBZ] from NASA EXRAD radar (nadir beam), (b) velocity $[m s^{-1}]$, and (c) spectrum width $[m s^{-1}]$ from NASA HIWRAP (Ka-band) radar. All vertical cross-sections are plotted with a 3:1 aspect ratio. Triangle icons next to (c) illustrate a 45° angle in a 1:1 and 3:1 aspect ratio. Corresponding NEXRAD regional map of (d) image muted reflectivity [dBZ] with ER-2 flight path in green and (e) feature detection classification with ER-2 flight path in purple, arrowhead denotes direction and location of aircraft at time of region map.



Figure 17. Vertical cross-section from 17 February 2022 20:13:11 to 20:34:43 UTC of (a) reflectivity [dBZ] from NASA HIWRAP (Kuband) radar, (b) velocity $[m s^{-1}]$, and (c) spectrum width $[m s^{-1}]$ from NASA CRS cloud radar. All vertical cross-sections are plotted with a 3:1 aspect ratio. Triangle icons next to (c) illustrate a 45° angle in a 1:1 and 3:1 aspect ratio. Corresponding NEXRAD regional map of (d) image muted reflectivity [dBZ] with ER-2 flight path in green and (e) feature detection classification with ER-2 flight path in purple, arrowhead denotes direction and location of aircraft at time of region map.



Figure 18. (a) Spectrum Width $[m s^{-1}]$, (b) Doppler Velocity $[m s^{-1}]$, and (c) Reflectivity [dBZ] RHIs from KaSPR radar at Stony Brook University at 15:58:42 UTC on 1 February 2021. RHIs are scanned up and over the radar (at 0 km on x-axis). Radar beam is partially blocked near edge of scan on right side. Plotted in a 1:1 aspect ratio. An animated version of this figure between 15:05-17:03 UTC is available in the Video Supplement Animation-Figure-18. An animation of the full storm is available in the Video Supplement Animation-Figure-18.



Figure 19. (a) Spectrum Width $[m s^{-1}]$, (b) Doppler Velocity $[m s^{-1}]$, and (c) Reflectivity [dBZ] RHIs from the KaSPR radar at Stony Brook University at 19:28:51 UTC on 1 February 2021. The RHIs are scanned up and over the radar (at 0 km on x-axis). Radar beam is partially blocked near edge of scan on right side. Plotted in a 1:1 aspect ratio. An animated version of this figure between 18:24-20:25 UTC is available in the Video Supplement Animation-Figure-19. An animation of the full storm is available in the Video Supplement Animation-Figure-19.

Table 1. Table of microphysical processes and their associated change to mass per unit volume (IWC and LWC), and radar reflectivity. Radar reflectivity is a function of diameter and dielectric constant. The dielectric constant is larger for liquid water than for ice particles.

Process	Change to mass per unit volume (IWC and LWC)	Change to radar reflectivity	Change to particle diameter	
Riming	Increase	Can increase ^{1,2}	Can increase ^{1,2}	
Vapor Deposition	Increase	Usually increase ¹	Increase	
Collision-Coalescence	Increase	Increase	Increase	
Condensation	Increase	Increase	Increase	
Aggregation	No change	Increase	Increase	
Melting	No change	Increase	Usually decrease ¹	
Evaporation	Decrease	Decrease	Decrease	
Sublimation	Decrease	Usually decrease ¹	Decrease	
Freezing	No change	Decrease	Usually increase ¹	
Ice Fragmentation	No change	Decrease	Decrease	
Raindrop breakup	No change	Decrease	Decrease	

¹ Depends on ice crystal shapes and densities of preexisting precipitation particles.

² Depends on degree of riming. For example, light riming will not change reflectivity or diameter much if at all.

785

Table 2. Band, frequency [GHz], sensitivity [dBZ] at 10 km, horizontal spatial resolution [m] at 10 km below the aircraft and vertical spatial resolution [m], and citation for radars deployed on the ER-2 aircraft during NASA IMPACTS. Band, frequency [GHz], sensitivity [dBZ] at 1 km, horizontal spatial resolution [m] at 10 km above the radar and vertical spatial resolution [m], and citation for KaSPR deployed at Stony Brook University during NASA IMPACTS.

Radars	Band	Frequency	Sensitivity	Spatial Resolution (H, V) Beamwide		Reference	
EXRAD (precip. radar)	Х	9.6 GHz	-9 dBZ	679 m, 110 m	3.4°	Heymsfield et al. (1996)	
HIWRAP	Ku	$13.5~\mathrm{GHz}$	$-17\mathrm{dBZ}$	672 m, 150 m	3.0°	L_{i} at al. (2016)	
(precip. radar)	Ka	$35.5~\mathrm{GHz}$	$-17\mathrm{dBZ}$	288 m, 150 m	1.2°	Li et al. (2010)	
CRS (cloud radar)	W	96 GHz	-34 dBZ	137 m, 115 m	0.64°	McLinden et al. (2021)	
KASPR (precip. radar)	Ka	35.3 GHz	-40 dBZ	56 m, 15 m	0.32°	Oue et al. (2024)	

Supplementary Material



Figure S1: An example transect of reflectivity from the EXRAD radar plotted with a (a) 3:1 aspect ratio and (b) 1:1 aspect ratio

Table S1: List of storm days between 1996-2023 used in the analysis. Dates are in YYYYMMDD format.

19960102	19960103	19960104	19960107	19960108	19960109	19960110	19960112
19960129	19960131	19960202	19960203	19960208	19960211	19960214	19960216
19960217	19960302	19960305	19960306	19960307	19960308	19960329	19961126
19961127	19961206	19961231	19970109	19970110	19970111	19970124	19970127
19970128	19970131	19970204	19970208	19970214	19970216	19970217	19970303
19970306	19970308	19970310	19970314	19970331	19971114	19971116	19971122
19971210	19971223	19971227	19971229	19971230	19980116	19980118	19980119
19980123	19980124	19980125	19980224	19980314	19980322	19981224	19981229
19981230	19990108	19990109	19990112	19990113	19990114	19990115	19990128
19990129	19990208	19990212	19990225	19990306	19990307	19990314	19990315
19990322	20000113	20000120	20000121	20000125	20000126	20000130	20000131
20000203	20000214	20000218	20000219	20000317	20001214	20001219	20001220
20001222	20001230	20001231	20010105	20010106	20010108	20010109	20010119
20010121	20010127	20010202	20010205	20010206	20010208	20010222	20010223
20010225	20010301	20010302	20010304	20010305	20010306	20010309	20010310
20010326	20010330	20011208	20011209	20020106	20020107	20020117	20020119
20020121	20020131	20020211	20020318	20020320	20021116	20021117	20021118
20021127	20021202	20021205	20021206	20021211	20021212	20021216	20021225
20021226	20030102	20030103	20030104	20030105	20030106	20030107	20030108
20030109	20030111	20030126	20030127	20030129	20030202	20030207	20030210
20030212	20030216	20030217	20030218	20030306	20030313	20030330	20031205
20031206	20031207	20031214	20031215	20031217	20040102	20040112	20040113
20040114	20040115	20040118	20040126	20040127	20040128	20040203	20040206
20040207	20040222	20040308	20040316	20040317	20040318	20040319	20041112
20041113	20041206	20041220	20041226	20041227	20050105	20050106	20050108
20050111	20050112	20050116	20050117	20050119	20050120	20050122	20050123
20050124	20050126	20050204	20050210	20050211	20050220	20050221	20050224
20050225	20050228	20050301	20050302	20050308	20050309	20050311	20050312
20050323	20050324	20051124	20051204	20051206	20051209	20051216	20051231
20060101	20060103	20060105	20060114	20060115	20060123	20060125	20060211
20060212	20060225	20060226	20060302	20070119	20070122	20070128	20070202
20070213	20070214	20070222	20070223	20070225	20070226	20070227	20070307
20070316	20070317	20070319	20070324	20071118	20071119	20071202	20071203
20071205	20071213	20071216	20071220	20071227	20071230	20071231	20080101
20080114	20080115	20080117	20080127	20080207	20080209	20080210	20080212
20080213	20080222	20080226	20080229	20080301	20080315	20080328	20081206
20081207	20081211	20081216	20081217	20081219	20081220	20081221	20081231
20090107	20090108	20090110	20090111	20090115	20090118	20090119	20090128
20090203	20090218	20090219	20090220	20090222	20090301	20090302	20090309
20091205	20091209	20091219	20091220	20091228	20091231	20100101	20100102
20100103	20100108	20100117	20100118	20100119	20100128	20100202	20100203

20100205	20100206	20100209	20100210	20100216	20100223	20100224	20100225
20100226	20100227	20101213	20101214	20101220	20101226	20101227	20110107
20110108	20110111	20110112	20110118	20110119	20110121	20110125	20110126
20110127	20110201	20110202	20110208	20110220	20110221	20110225	20110227
20110307	20110321	20110323	20110324	20110331	20111027	20111029	20111030
20111207	20120112	20120116	20120117	20120119	20120120	20120121	20120224
20120229	20120301	20121107	20121108	20121127	20121221	20121222	20121225
20121226	20121227	20121229	20130116	20130121	20130125	20130128	20130208
20130209	20130216	20130217	20130224	20130227	20130307	20130308	20130318
20130319	20131112	20131126	20131206	20131208	20131210	20131214	20131215
20131217	20131224	20131226	20131229	20140102	20140103	20140110	20140118
20140121	20140122	20140125	20140129	20140203	20140205	20140209	20140213
20140214	20140215	20140218	20140219	20140313	20141114	20141126	20141127
20141209	20141210	20141211	20150103	20150106	20150109	20150112	20150124
20150126	20150127	20150130	20150131	20150201	20150202	20150205	20150208
20150209	20150212	20150214	20150215	20150217	20150218	20150219	20150221
20150222	20150225	20150301	20150303	20150305	20150315	20150320	20150321
20150328	20151229	20160112	20160117	20160118	20160122	20160123	20160205
20160208	20160209	20160210	20160215	20160321	20161027	20161119	20161120
20161205	20161212	20161217	20161229	20161230	20170106	20170107	20170114
20170118	20170124	20170131	20170201	20170207	20170209	20170211	20170212
20170213	20170215	20170216	20170310	20170313	20170314	20170315	20170331
20171209	20171212	20171213	20171214	20171215	20171222	20171225	20171230
20180104	20180113	20180116	20180117	20180130	20180201	20180204	20180207
20180217	20180218	20180222	20180302	20180307	20180308	20180309	20180312
20180313	20180314	20180321	20180322	20181115	20181116	20181119	20181120
20181127	20181213	20190109	20190119	20190120	20190129	20190130	20190212
20190218	20190220	20190221	20190227	20190228	20190301	20190302	20190303
20190304	20190310	20190322	20191112	20191201	20191202	20191203	20191206
20191211	20191217	20191218	20191230	20200116	20200118	20200119	20200202
20200206	20200207	20200209	20200213	20200218	20200323	20201030	20201205
20201209	20201216	20201217	20201220	20201225	20210101	20210102	20210103
20210126	20210127	20210131	20210201	20210202	20210203	20210207	20210209
20210211	20210218	20210219	20210222	20211126	20211128	20211208	20211218
20211219	20211224	20220107	20220116	20220117	20220124	20220128	20220129
20220204	20220213	20220214	20220225	20220309	20220312	20221115	20221211
20221215	20221216	20230106	20230116	20230120	20230122	20230123	20230125
20230222	20230223	20230225	20230227	20230228	20230303	20230304	20230311
20230314							

All available transects from NASA IMPACTS with snow to the surface

In this section we present all 57 available transects from the 3 NASA IMPACTS deployment which have snow to the surface. For each transect we present the reflectivity, velocity, spectrum width, and LDR fields from the instrument with the shortest wavelength available (usually CRS, but occasionally HIWRAP Ku-band) and the reflectivity field from the instrument with the longest wavelength available (usually EXRAD, but occasionally HIWRAP Ka-band). We include snapshots of the NEXRAD regional maps to provide context for the transects. If available, we include the VAD winds on the EXRAD reflectivity transects and CFADs of wind speed and direction to summarize the wind patterns. Each transect is annotated with one or two vertical, dashed, black lines which annotates the approximate location where the enhanced reflectivity features are in the regional maps. The time of the regional maps and transects as well as the field and instrument plotted is labeled above each sub-figure.









































Distance [km] →











































































